



Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Device application	Lightweight installation
Drilling diameter	6 Mm concrete 6 Mm brick 6 mm ALC concrete
Minimum drilling depth	35 mm
Screw diameter	3,5...5 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	Shear 0,6 kN concrete C25 4,5) Pull-out load 0,4 kN concrete C25 6) Shear 0,5 kN solid brick 4,5) Pull-out load 0,3 kN solid brick 6) Shear 0,2 kN low density concrete 500 and expanded clay 4,5) Pull-out load 0,08 kN low density concrete 500 and expanded clay 6)
Practical load capacity	Shear 60 kg concrete C25 4,5) Pull-out load 40 kg concrete C25 6) Shear 50 kg solid brick 4,5) Pull-out load 30 kg solid brick 6) Shear 20 kg low density concrete 500 and expanded clay 4,5) Pull-out load 8 kg low density concrete 500 and expanded clay 6)
Colour tint	Red
Ambient air temperature for operation	-50...80 °C
Diameter	6 mm
Length	30 mm

Environment

Quantity per set	Set of 100
Sale per indivisible quantity	1
Net weight	0,00068 kg

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	13 cm
Pakendi laius 1	10 cm
Pakendi pikkus 1	22 cm
Pakendi kaal 1	0,68 g

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Ennetav vastavus (toode ei jää EL-i RoHS seadustega määratud piiridesse) ELi RoHS deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnavalade avaldus	Toote Keskkonnaprofiil

Contractual warranty

Garantii	18 months
----------	-----------