



Main

Range	Renova
Range of product	Renova
Device short name	SBD200LED
Product or component type	Dimmer
Device application	Light control
Device presentation	Mechanism with fixing frame
Colour	black

Complementary

Device mounting	Flush
Fixing mode	By screws
Dimmer type	Universal
Dimmer control	Rotary push type
Control type	Rotary push type
Switch function	1-pole 2-way
Load type	Incandescent lamp 230 V halogen lamp LED lamp Low voltage halogen lamp with ferromagnetic transformer Low voltage halogen lamp with electronic transformer
Power range	Halogen lamp 4...400 W Incandescent lamp 4...400 W LED lamp 4...40 W RL LED mode) LED lamp 4 W...200 VA RC LED mode) Low voltage halogen lamp with electronic transformer 4...400 W Low voltage halogen lamp with ferromagnetic transformer 4 W...400 VA
[Ue] rated operational voltage	230 V AC 50/60 Hz
Rated current/voltage	10 A 230 V AC
Protection type	Electronic short-circuit and automatic overload protection
Connections - terminals	Screw terminals
Number of loop terminals	1
Clamping connection capacity	1 x 2.5 mm ² solid or flexible with sleeve 2 x 1.5 mm ² solid or flexible with sleeve
Material	Thermoplastic
Embedding depth	29 mm
Height	71 mm
Width	71 mm
Depth	51 mm
Diameter	71 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	5...95 %
IP degree of protection	IP20 also with visual parts removed

Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	8,0 cm
Pakendi laius 1	9,4 cm
Pakendi pikkus 1	9,8 cm
Pakendi kaal 1	136,0 g
Pakendi tüüp 2	CAR
Ühikute arv pakendis 2	10
Pakendi kõrgus 2	10,0 cm
Pakendi laius 2	20,0 cm
Pakendi pikkus 2	40,0 cm
Pakendi kaal 2	1,464 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnaalane avaldus	Toote Keskkonnaprofiil
Ringlusprofiil	Kasutuselt Kõrvaldamise Teave
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.