



Main

Range	Renova
Product or component type	Socket-outlet
Device presentation	Mechanism with fixing frame
Quantity per set	Set of 5
Product compatibility	To be completed with Renova frame

Complementary

Socket number	1
Device mounting	Flush
Outlet poles configuration	2P + E
Outlet standard deviation	Schuko
Outlet standard	CEE 7/3
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Colour tint	White RAL 9010)
Connections - terminals	Screwless terminals
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² solid 1 x 1.5...2 x 2.5 mm ² solid stranded
Material	PC/ABS
Fixing mode	By screws and claws
Diameter	71 mm
Embedding depth	28 mm
Projecting depth	15 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 SS 4280834 SFS 5610:2004
Product certifications	FIMKO SEMKO
IP degree of protection	IP20

Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	4,0 cm
Pakendi laius 1	7,1 cm
Pakendi pikkus 1	7,1 cm
Pakendi kaal 1	67,0 g
Pakendi tüüp 2	Gyári csomagolás
Ühikute arv pakendis 2	5

Pakendi kõrgus 2	8,5 cm
Pakendi laius 2	8,5 cm
Pakendi pikkus 2	22,5 cm
Pakendi kaal 2	394,0 g
Pakendi tüüp 3	CAR
Ühikute arv pakendis 3	80
Pakendi kõrgus 3	32,5 cm
Pakendi laius 3	30,0 cm
Pakendi pikkus 3	40,0 cm
Pakendi kaal 3	6,77 kg

Offer Sustainability

ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnavalendavaldus	Toote Keskkonnaprofiil
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.