



Main

Range	Renova
Product or component type	Thermostat
Device presentation	Mechanism with fixing frame
Colour tint	white
Quantity per set	Set of 1
Product compatibility	To be completed with Renova frame

Complementary

Device mounting	Flush
Device application	Room
Switch function	2-pole
Temperature setting range	5...30 °C
Rated current	16 A 250 V AC
Local signalling	Heating application LED red) Operating LED green)
Connections - terminals	Screw clamp terminal
Material	PC/ABS
Embedding depth	24 mm
Diameter	83 mm
Projecting depth	21 mm

Environment

IP degree of protection	IP20
-------------------------	------

Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	5,6 cm
Pakendi laius 1	7,8 cm
Pakendi pikkus 1	8,4 cm
Pakendi kaal 1	128,0 g
Pakendi tüüp 2	Gyári csomagolás
Ühikute arv pakendis 2	12
Pakendi kõrgus 2	11,8 cm
Pakendi laius 2	16,8 cm
Pakendi pikkus 2	25,2 cm
Pakendi kaal 2	1,538 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnavalade avaldus	Toote Keskkonnaprofiil
Ringlusprofiil	Kasutuselt Kõrvaldamise Teave
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.