

Main

Range	Renova
Product or component type	Dimmer
Device application	Light control
Device presentation	Mechanism with fixing frame and central plate
Dimmer type	Universal
Load type	Incandescent lamp 40...420 W 230 V AC halogen lamp 40...420 W Low voltage halogen lamp with electronic transformer 40...420 W Conventional transformer 40...420 W
Colour	White RAL 9010)
Quantity per set	Set of 1

Complementary

Product compatibility	To be completed with Renova frame
[Ue] rated operational voltage	230 V AC
Rated current	10 A
Power range	40...420 W
Switch function	1-pole 2-way
Dimmer control	Rotary push type
Protection type	Electronic short-circuit and automatic overload protection
Connections - terminals	Screw terminals
Number of loop terminals	1
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² solid 1 x 1.5...2 x 2.5 mm ² solid stranded
Material	PC/ABS
Device mounting	Flush
Diameter	71 mm
Embedding depth	29 mm
Projecting depth	22 mm

Environment

IP degree of protection	IP20
Standards	EN 60669-1 EN 60669-2-1

Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	8,0 cm
Pakendi laius 1	9,6 cm
Pakendi pikkus 1	9,8 cm
Pakendi kaal 1	126,0 g
Pakendi tüüp 2	CAR
Ühikute arv pakendis 2	10
Pakendi kõrgus 2	10,0 cm

Pakendi laius 2	20,0 cm
Pakendi pikkus 2	40,2 cm
Pakendi kaal 2	1,368 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	 REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus  ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	 Hiina RoHS Deklaratsioon
RoHS eranditeave	 Jah
Keskkonnavalade avaldus	 Toote Keskkonnaprofiil
Ringlusprofiil	 Kasutuselt Kõrvaldamise Teave
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.