



Main

Range	Renova
Product or component type	Socket-outlet
Device presentation	Mechanism with fixing frame
Quantity per set	Set of 5
Product compatibility	To be completed with Renova frame

Complementary

Socket number	2
Device mounting	Flush
Outlet poles configuration	2P + E
Outlet standard deviation	Schuko
Outlet standard	CEE 7/3
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Colour tint	Black NCS S 9000-N)
Connections - terminals	Screw terminals
Number of loop terminals	2
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² solid 1 x 1.5...2 x 2.5 mm ² solid stranded
Material	PC/ABS
Fixing mode	By screws and claws
Width	71 mm
Height	92 mm
Embedding depth	22 mm
Projecting depth	22 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 SS 4280834 SFS 5610:2004 NEK 502:2006
Product certifications	SEMKO NEMKO FIMKO
IP degree of protection	IP20

Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	4,9 cm
Pakendi laius 1	9,6 cm
Pakendi pikkus 1	7 cm
Pakendi kaal 1	88 g
Pakendi tüüp 2	Gyári csomagolás
Ühikute arv pakendis 2	5
Pakendi kõrgus 2	10,6 cm
Pakendi laius 2	9,4 cm
Pakendi pikkus 2	25,8 cm
Pakendi kaal 2	510 g
Pakendi tüüp 3	CAR
Ühikute arv pakendis 3	60
Pakendi kõrgus 3	34,2 cm
Pakendi laius 3	29,2 cm
Pakendi pikkus 3	39 cm
Pakendi kaal 3	6,6 kg

Offer Sustainability

Jätksuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnavalade avaldus	Toote Keskkonnaprofiil