



### Main

Range	Renova
Product or component type	Dimmer
Device application	Light control
Device presentation	Mechanism with fixing frame and central plate
Dimmer type	Transistor
Load type	230 V AC halogen lamp 40...300 W Incandescent lamp 40...315 W Low voltage halogen lamp with electronic transformer 40...315 W
Colour	Black NCS S 9000-N)
Quantity per set	Set of 1

### Complementary

[Ue] rated operational voltage	230 V
Rated current	10 A
Power range	40...315 W 40...300 W
Switch function	1-pole 2-way
Dimmer control	Rotary
Protection type	Short-circuit and overload protection with automatic reset
Connections - terminals	Screw terminals
Number of loop terminals	1
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> solid 1 x 1.5...2 x 2.5 mm <sup>2</sup> solid stranded
Material	PC/ABS
Device mounting	Flush
Diameter	83 mm
Embedding depth	29 mm
Projecting depth	22 mm

### Environment

IP degree of protection	IP20
Standards	EN 60669-2-1 EN 60669-1

### Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	8,2 cm
Pakendi laius 1	9,8 cm
Pakendi pikkus 1	9,8 cm
Pakendi kaal 1	126,0 g
Pakendi tüüp 2	CAR
Ühikute arv pakendis 2	10
Pakendi kõrgus 2	10,2 cm
Pakendi laius 2	20,0 cm

Pakendi pikkus 2	39,8 cm
Pakendi kaal 2	1,368 kg

## Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	<a href="#">REACH-deklaratsioon</a>
ELi RoHS direktiiv	Vastavus <a href="#">ELi RoHS Deklaratsioon</a>
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	<a href="#">Hiina RoHS Deklaratsioon</a>
RoHS eranditeave	<a href="#">Jah</a>
Keskkonnavalade avaldus	<a href="#">Toote Keskkonnaprofiil</a>
Ringlusprofiil	<a href="#">Kasutuselt Kõrvaldamise Teave</a>
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.