



### Main

Range	Renova
Product or component type	Thermostat
Device presentation	Mechanism with fixing frame
Colour tint	black
Quantity per set	Set of 1
Product compatibility	To be completed with Renova frame

### Complementary

Device mounting	Flush
Device application	Floor
Switch function	2-pole
Temperature setting range	5...30 °C
Rated current	16 A 250 V AC
Local signalling	Heating application LED (red) Operating LED (green)
Connections - terminals	Screw clamp terminal
Material	PC/ABS
Embedding depth	24 mm
Diameter	83 mm
Projecting depth	21 mm

### Environment

IP degree of protection	IP20
-------------------------	------

### Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	8 cm
Pakendi laius 1	9,7 cm
Pakendi pikkus 1	9,7 cm
Pakendi kaal 1	186 g
Pakendi tüüp 2	CAR
Ühikute arv pakendis 2	10
Pakendi kõrgus 2	10,1 cm
Pakendi laius 2	20,1 cm
Pakendi pikkus 2	40,4 cm
Pakendi kaal 2	2,004 kg

## Offer Sustainability

Jätksuutliku pakkumise olek	Green Premium toode
REACH-määrus	<a href="#">REACH-deklaratsioon</a>
ELi RoHS direktiiv	Vastavus <a href="#">ELi RoHS Deklaratsioon</a>
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	<a href="#">Hiina RoHS Deklaratsioon</a>
RoHS eranditeave	<a href="#">Jah</a>
Keskkonnavalade avaldus	<a href="#">Toote Keskkonnaprofiil</a>
Ringlusprofiil	<a href="#">Kasutuselt Kõrvaldamise Teave</a>
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.