



Main

Range	Renova
Product or component type	Socket-outlet
Device presentation	Complete product
Quantity per set	Set of 10

Complementary

Socket number	2
Device mounting	Surface
Outlet poles configuration	2P + E
Outlet standard deviation	Schuko
Outlet standard	CEE 7/3
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Colour tint	White RAL 9010)
Connections - terminals	Screwless terminals
Number of loop terminals	2,0
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² solid 1 x 1.5...2 x 2.5 mm ² solid stranded
Material	PC (polycarbonate) cover frame PC 10 % GF bottom-plate
Fixing mode	By screws insert By screws cover frame
Width	70,0 mm
Height	111,0 mm
Embedding depth	0,0 mm
Projecting depth	43,0 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 NEK 502 SFS 5610 SS 4280834
Product certifications	FIMKO NEMKO SEMKO CE
IP degree of protection	IP20

Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	4,3 cm
Pakendi laius 1	6,9 cm
Pakendi pikkus 1	11 cm
Pakendi kaal 1	102 g
Pakendi tüüp 2	Gyári csomagolás
Ühikute arv pakendis 2	10
Pakendi kõrgus 2	11,9 cm
Pakendi laius 2	18,1 cm
Pakendi pikkus 2	25,9 cm
Pakendi kaal 2	1,136 kg

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.