



### Main

Range	Renova
Product or component type	Switch
Device application	Light control
Device presentation	Complete product
Colour	Black NCS S 9000-N)
Quantity per set	Set of 5
Switch function	1-pole 2-way

### Complementary

Technology type	Electromechanical
Rated current	16 AX
[Ue] rated operational voltage	250 V AC
Connections - terminals	Screwless terminals
Number of loop terminals	2
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> solid 1 x 1.5...2 x 2.5 mm <sup>2</sup> solid stranded
Device mounting	Surface
Number of rocker	1
Switch pattern	[6/1]
Actuator	Rocker
Material	PC cover PC 10 % GF bottom-plate PC/ABS rocker
Surface finish	Cover plate glossy Cover frame matt
Fixing mode	By screw
Diameter	70,0 mm
Embedding depth	0,0 mm
Projecting depth	27,0 mm
IP degree of protection	IP20 IP21 when cable is coming from below
Product certifications	CE FIMKO NEMKO SEMKO
Standards	EN 60669-1

### Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	3,5 cm
Pakendi laius 1	6,9 cm
Pakendi pikkus 1	6,9 cm
Pakendi kaal 1	58 g
Pakendi tüüp 2	Gyári csomagolás

Ühikute arv pakendis 2	5
Pakendi kõrgus 2	8,8 cm
Pakendi laius 2	8,8 cm
Pakendi pikkus 2	22,8 cm
Pakendi kaal 2	344 g
Pakendi tüüp 3	CAR
Ühikute arv pakendis 3	140
Pakendi kõrgus 3	29,8 cm
Pakendi laius 3	39 cm
Pakendi pikkus 3	58,8 cm
Pakendi kaal 3	10,438 kg

## Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	<a href="#">REACH-deklaratsioon</a>
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus <a href="#">ELi RoHS Deklaratsioon</a>
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
RoHS eranditeave	<a href="#">Jah</a>
Hiina EoHS regulatsioon	<a href="#">Hiina RoHS Deklaratsioon</a>
Keskkonnaalane avaldus	<a href="#">Toote Keskkonnaprofiil</a>
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.