

NSYTRV352PE

SCREW TERMINAL, PROTECTIVE EARTH, 2 POINTS, 35MM², GREEN-YELLOW



Main

Range	Lineryg
Product name	Lineryg TR
Product or component type	Terminal block
Device short name	TRV
Terminal block type	Protective earth
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	35 mm ²
Length	65,7 mm
Colour	Green-yellow
Quantity per set	Set of 50

Complementary

Width	16 mm
Height	60,2 mm
Connections - terminals	1 x screw terminal upstream 1 x screw terminal downstream
Number of connections	2
Connection position	Sideways
Number of measurement input	2
Cable cross section	1,5...50 Mm ² , solid 2,5...35 Mm ² , flexible with cable end 1,5...50 mm ² , flexible without cable end
Tightening torque	3,2...3,7 N.m
Wire stripping length	18 mm
Tool type	Connection screwdriver Disconnection screwdriver
[In] rated current	125 A EN/IEC 60947-7-1
Material	Polyamide 6/6 insulating case
Dielectric loss	0,01 at 1 MHz IEC 60250 0,01 at 1 MHz VDE 0303-T4
Dielectric constant	3,7 at 1 MHz
Resistivity	10000 MΩ.M IEC 60093 10000 MΩ.m VDE 0303-T30
Surface resistance	1000 GΩ IEC 60093 1000 GΩ VDE 0303-T30
Creep resistance	500 CTI (> 400 kV) IEC 60093 500 CTI (> 400 kV) VDE 0303-T30
Flame retardance	V0 0,8 mm UL 94
Net weight	85,79 g
Range compatibility	Prisma G Prisma P Prisma PH Prisma Pack Spacial Kaedra Pragma TeSys
Product compatibility	Spacial enclosures

Environment

Product certifications	VDE EAC CSA CURus IEC-Ex GL ATEX
Dielectric strength	1000 V IEC 60243-1
Ambient air temperature for operation	-40...130 °C IEC 60216-1 -40...130 °C VDE 0304-T21

Pakke osad

Pakendi tüüp 1	Db
Ühikute arv pakendis 1	1
Package 1 Height	9,500 cm
Pakendi laius 1	18,000 cm
Pakendi pikkus 1	28,000 cm
Pakendi kaal 1	85,000 g
Pakendi tüüp 2	Gyári csomagolás
Ühikute arv pakendis 2	50
Pakendi kõrgus 2	9,500 cm
Pakendi laius 2	18,000 cm
Pakendi pikkus 2	28,000 cm
Pakendi kaal 2	4,418 kg
Pakendi tüüp 3	P06
Ühikute arv pakendis 3	1700
Pakendi kõrgus 3	75,000 cm
Pakendi laius 3	60,000 cm
Pakendi pikkus 3	80,000 cm
Pakendi kaal 3	161,580 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	 REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus  ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	 Hiina RoHS Deklaratsioon
RoHS eranditeave	 Jah
Keskkonnaalane avaldus	 Toote Keskkonnaprofiil
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.
Halogeensisu	Halogeenivabade plastosadega toode

Contractual warranty

Garantii	18 months
----------	-----------