HellermannTyton

| | | Material Datasheet | 27.03.202 |
|----------------------|-----------------|-------------------------|-----------|
| | FLEX15-15x10 | | |
| Article N | umber 710-00108 | 3 | |
| Material: | | Polyvinylchloride (PVC) | |
| Colour: | | Grey (GY) | |
| Operating T | emperature : | -10 °C to +90 °C | |
| Thickness (1 | Г): | 0.15 mm | |
| Width (W): | | 15 mm | |
| Length (L): | | 10 m | |
| Breaking Strength: | | 28 N/10 mm | |
| Adhesion to Backing: | | 2.0 N/10 mm | |
| Adhesion to | Steel: | 2.2 N/10 mm | |
| Elongation a | at break: | 200 % | |
| Dielectric St | | 45 kV/mm | |
| Shelf Life: | | 5 years | |
| Storage Ten | nperature: | +23 °C | |
| RoHS | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved