



Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Device application	Lightweight installation
Drilling diameter	5,5 Mm concrete 5,5 Mm brick 5 mm ALC concrete
Minimum drilling depth	25 mm
Screw diameter	3,5...5 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	Shear 0,5 kN concrete C25 4,5) Pull-out load 0,25 kN concrete C25 6) Shear 0,4 kN solid brick 4,5) Pull-out load 0,2 kN solid brick 6) Shear 0,1 kN low density concrete 500 and expanded clay 4,5) Pull-out load 0,04 kN low density concrete 500 and expanded clay 6)
Practical load capacity	Shear 50 kg concrete C25 4,5) Pull-out load 25 kg concrete C25 6) Shear 40 kg solid brick 4,5) Pull-out load 20 kg solid brick 6) Shear 10 kg low density concrete 500 and expanded clay 4,5) Pull-out load 4 kg low density concrete 500 and expanded clay 6)
Colour tint	Yellow
Ambient air temperature for operation	-50...80 °C
Diameter	5,5 mm
Length	22 mm

Environment

Quantity per set	Set of 100
Sale per indivisible quantity	1
Net weight	0,00035 kg

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	11,4 cm
Pakendi laius 1	8,6 cm
Pakendi pikkus 1	20,5 cm
Pakendi kaal 1	0,35 g

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Ennetav vastavus (toode ei jää EL-i RoHS seadustega määratud piiridesse) ELi RoHS deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnavalade avaldus	Toote Keskkonnaprofiil

Contractual warranty

Garantii	18 months
----------	-----------