



Main

Range name	Sedna Design & Elements
Range	Sedna
Device application	Control
Product or component type	Switch
Function	Double 2-way
Delivery form	Mechanism with fixing frame
Rated current	10 AX 250 V AC
Colour	White
Colour code	RAL 9003

Complementary

Load type	1 lamp integrated ballast 100 W)
Kind of terminals	Screwless terminals
Targeted channel	Professional
Accessory / separate part type	Claw and screw for mechanism
Power range	2300 W
Device mounting	Flush
Cable cross section	2,5 mm ²
Wire structure	Rigid
Wire stripping length	13 mm
Material of visible parts	Thermoplastic ABS-UV stabilised
Surface finish	Glossy
Fixing mode	Claws, span of claws working range 51...70 mm Claws, span of claws working range 52...68 mm Screws
Height	73 mm
Width	73 mm
Depth	37 mm
Depth of visual part	24 mm
Net weight	0,061 kg

Environment

IP degree of protection	IP20
Conformity mark	CE
Product certifications	GOST-R
Standards	IEC 60669-1

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	4,0 cm
Pakendi laius 1	7,5 cm
Pakendi pikkus 1	7,5 cm
Pakendi kaal 1	68,0 g
Pakendi tüüp 2	BB1

Ühikute arv pakendis 2	10
Pakendi kõrgus 2	9,5 cm
Pakendi laius 2	18,5 cm
Pakendi pikkus 2	27,5 cm
Pakendi kaal 2	764,0 g
Pakendi tüüp 3	S04
Ühikute arv pakendis 3	120
Pakendi kõrgus 3	30,0 cm
Pakendi laius 3	40,0 cm
Pakendi pikkus 3	60,0 cm
Pakendi kaal 3	9,809 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnavalade avaldus	Toote Keskkonnaprofiil