



Main

Range name	Sedna Design & Elements
Range	Sedna
Function	Socket-outlet
Device mounting	Flush
Delivery form	Complete product
Type of packing	Flow-pack
Outlet poles configuration	2 x 2P + E with shutters
Outlet standard description	Side earth
Outlet standard deviation	European
Rated current	16 A 250 V AC
Colour	Beige
Colour code	RAL 1013
Quantity per set	1 piece

Complementary

Power range	3680 W
Kind of terminals	Screwless terminals
Terminal capacity	2 2,5 mm ²
Wire structure	Rigid
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Glossy
Fixing mode	Screws or claws, span of claws working range 52...77 mm Claws, span of claws working range 52...69 mm
Height	85 mm
Width	120 mm
Depth	49 mm
Depth of visual part	24 mm
Net weight	0,095 kg

Environment

Standards	IEC 60884-1
Conformity mark	CE EAC
Product certifications	VDE AENOR
IP degree of protection	IP20

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	5 cm
Pakendi laius 1	8,5 cm
Pakendi pikkus 1	12 cm

Pakendi kaal 1	99 g
Pakendi tüüp 2	BB1
Ühikute arv pakendis 2	8
Pakendi kõrgus 2	9,5 cm
Pakendi laius 2	18,5 cm
Pakendi pikkus 2	27,5 cm
Pakendi kaal 2	872 g
Pakendi tüüp 3	S04
Ühikute arv pakendis 3	96
Pakendi kõrgus 3	30 cm
Pakendi laius 3	40 cm
Pakendi pikkus 3	60 cm
Pakendi kaal 3	11,105 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	 REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus  ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	 Hiina RoHS Deklaratsioon
RoHS eranditeave	 Jah
Keskkonnaalane avaldus	 Toote Keskkonnaprofiil
Halogeensisu	Halogeenivaba toode