



Main

Range name	Sedna Design & Elements
Range	Sedna
Function	USB charger + socket-outlet
Device mounting	Flush
Delivery form	Mechanism with fixing frame
Type of packing	Box
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard deviation	European
Rated current	16 A 250 V AC
Colour	Beige
Colour code	RAL 1013
Quantity per set	1 piece

Complementary

Power range	3680 W
Integrated connection type	2 USB 2.0 port 5 V DC 2.1 A
Kind of terminals	Screwless terminals
Terminal capacity	2 2,5 mm ²
Wire structure	Rigid or flexible
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Glossy
Fixing mode	Screws or claws, span of claws working range 55...67 mm Claws, span of claws working range 52...69 mm
Height	71 mm
Width	71 mm
Depth	44 mm
Depth of visual part	32 mm
Net weight	0,096 kg

Environment

Standards	IEC 60884-1
Conformity mark	CE KEMA-KEUR EAC
Product certifications	VDE FIMKO NEMKO AENOR
IP degree of protection	IP20

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	6,0 cm
Pakendi laius 1	7,5 cm
Pakendi pikkus 1	7,5 cm
Pakendi kaal 1	117,0 g
Pakendi tüüp 2	S03
Ühikute arv pakendis 2	54
Pakendi kõrgus 2	30,0 cm
Pakendi laius 2	30,0 cm
Pakendi pikkus 2	40,0 cm
Pakendi kaal 2	6,741 kg
Pakendi tüüp 3	P12
Ühikute arv pakendis 3	864
Pakendi kõrgus 3	75,0 cm
Pakendi laius 3	80,0 cm
Pakendi pikkus 3	120,0 cm
Pakendi kaal 3	119,856 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	 REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus  ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	 Hiina RoHS Deklaratsioon
RoHS eranditeave	 Jah
Keskkonnaalane avaldus	 Toote Keskkonnaprofiil
Halogeensisu	Halogeenivaba toode