



### Main

|                            |                                                        |
|----------------------------|--------------------------------------------------------|
| Range of product           | Sedna Design & Elements                                |
| Product or component type  | USB charger                                            |
| Colour code                | RAL 1013                                               |
| Colour                     | Beige                                                  |
| Integrated connection type | 1 USB type C 5 V DC 2.4 A<br>1 USB type A 5 V DC 2.1 A |

### Complementary

|                                |                                                                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Device application             | Charger                                                                                                                                |
| Device mounting                | Flush                                                                                                                                  |
| Device presentation            | Mechanism with fixing frame                                                                                                            |
| Surface finish                 | Glossy                                                                                                                                 |
| Surface treatment              | Untreated                                                                                                                              |
| Output current                 | 2.4 A                                                                                                                                  |
| Fixing mode                    | By screws                                                                                                                              |
| Type of packing                | Flow-pack                                                                                                                              |
| Connector type                 | USB type A<br>USB type C                                                                                                               |
| [Ue] rated operational voltage | 100...240 V AC +/- 10 % 50/60 Hz                                                                                                       |
| Power consumption in W         | 0,075 W                                                                                                                                |
| Nominal output power           | 12 W                                                                                                                                   |
| Input power                    | 12 W                                                                                                                                   |
| Service life in hours          | 30000 h 12 W                                                                                                                           |
| Material                       | ABS (acrylonitrile butadiene-styrene) centre plate<br>PC (polycarbonate) GF10 FR casing<br>PC (polycarbonate) GF10 FR internal cover   |
| Protection type                | Short-circuit protection                                                                                                               |
| Number of terminals            | 2 screw terminals                                                                                                                      |
| Clamping connection capacity   | 2 x 0.75...2 x 2.5 mm <sup>2</sup> rigid<br>2 x 0.75...2 x 2.5 mm <sup>2</sup> flexible<br>2 x 0.75...2 x 2.5 mm <sup>2</sup> stranded |
| Wire stripping length          | 8 mm                                                                                                                                   |
| Product compatibility          | Mobile/Tablet Mac iOS<br>Mobile/Tablet Android<br>Mobile/tablet Windows                                                                |
| Height                         | 73 mm                                                                                                                                  |
| Width                          | 73 mm                                                                                                                                  |
| Depth                          | 43 mm                                                                                                                                  |
| Embedding depth                | 31 mm                                                                                                                                  |
| Net weight                     | 0,082 kg                                                                                                                               |
| Targeted channel               | Professional                                                                                                                           |

## Environment

|                                       |                   |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...40 °C         |
| Ambient air temperature for storage   | -5...50 °C        |
| Standards                             | ETSI EN 301 489-4 |
| Product certifications                | EAC               |
| Electrical insulation class           | Class II          |
| IK degree of protection               | IK04              |
| IP degree of protection               | IP20              |

## Pakke osad

|                        |          |
|------------------------|----------|
| Pakendi tüüp 1         | PCE      |
| Ühikute arv pakendis 1 | 1        |
| Package 1 Height       | 6,2 cm   |
| Pakendi laius 1        | 8,3 cm   |
| Pakendi pikkus 1       | 8,3 cm   |
| Pakendi kaal 1         | 115,0 g  |
| Pakendi tüüp 2         | CAR      |
| Ühikute arv pakendis 2 | 36       |
| Pakendi kõrgus 2       | 18,5 cm  |
| Pakendi laius 2        | 30,0 cm  |
| Pakendi pikkus 2       | 40,0 cm  |
| Pakendi kaal 2         | 4,545 kg |

## Offer Sustainability

|                             |                                                                                                                                     |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Jätksuutliku pakkumise olek | Green Premium toode                                                                                                                 |
| REACH-määrus                |  <a href="#">REACH-deklaratsioon</a>             |
| ELi RoHS direktiiv          | Vastavus  <a href="#">ELi RoHS Deklaratsioon</a> |
| Elavhõbedavaba              | Jah                                                                                                                                 |
| Hiina EoHS regulatsioon     |  <a href="#">Hiina RoHS Deklaratsioon</a>        |
| RoHS eranditeave            |  <a href="#">Jah</a>                             |
| Keskkonnaalane avaldus      |  <a href="#">Toote Keskkonnaprofiil</a>          |