



Main

Range	Sedna
Product or component type	Switch
Device presentation	Mechanism with fixing frame
Device application	Control
Switch function	2-way

Complementary

Device mounting	Flush
Load type	1 lamp integrated ballast 100 W)
Surface finish	Painted
Kind of terminals	Screwless terminals
Accessory / separate part type	Claw and screw for mechanism
Power range	2300 W
Cable cross section	2,5 mm ²
Wire structure	Rigid
Wire stripping length	13 mm
Fixing mode	Claws, span of claws working range 51...70 mm Claws, span of claws working range 52...68 mm Screws
Height	73 mm
Width	73 mm
Depth	37 mm
Depth of visual part	24 mm
Net weight	0,058 kg
Targeted channel	Professional

Environment

IP degree of protection	IP20
Conformity mark	CE
Product certifications	GOST-R
Standards	IEC 60669-1

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	3,0 cm
Pakendi laius 1	7,0 cm
Pakendi pikkus 1	7,0 cm
Pakendi kaal 1	61,0 g
Pakendi tüüp 2	BB1
Ühikute arv pakendis 2	10

Pakendi kõrgus 2	9,5 cm
Pakendi laius 2	19,0 cm
Pakendi pikkus 2	27,5 cm
Pakendi kaal 2	698,0 g
Pakendi tüüp 3	S04
Ühikute arv pakendis 3	120
Pakendi kõrgus 3	30,0 cm
Pakendi laius 3	40,0 cm
Pakendi pikkus 3	60,0 cm
Pakendi kaal 3	9,04 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	 REACH-deklaratsioon
Ilma SVHC REACH-ta	Jah
ELi RoHS direktiiv	Vastavus  ELi RoHS Deklaratsioon
Mürgiste raskemetallideta	Jah
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	 Hiina RoHS Deklaratsioon
RoHS eranditeave	 Jah
Keskkonnavalade avaldus	 Toote Keskkonnaprofiil