



Main

Range of product	Sedna Design & Elements
Product or component type	Dimmer
Device presentation	Mechanism with fixing frame
Device application	Light control
Colour tint	anthracite
Kind of terminals	Screw terminal

Complementary

Device mounting	Flush
Dimmer control	Rotary push type
Load type	Halogen lamp 14...150 W Halogen lamp 5...150 W Incandescent lamp 14...200 W Incandescent lamp 5...200 W LV halogen lamps 14...150 VA LV halogen lamps 5...150 VA LED lamp 7...100 VA LED lamp 5...100 VA LED lamp 7...20 VA LED lamp 5...20 VA
Rated voltage	230 V AC 12 V AC
Protection type	Overheating protection Automatic overload protection Short-circuit protection
Main colour tint	Anthracite
Material	Polycarbonate
Surface finish	Painted
Control type	Local control Remote control
Fixing mode	By screws
Height	73 mm
Width	73 mm
Depth	55 mm
Net weight	0,093 kg
Market segment	Small buildings Residential

Environment

Standards	EN 60669-2-5 IEC 60669-2-5
Conformity mark	CE EAC
Product certifications	CE EAC
IP degree of protection	IP20
Ambient air temperature for operation	5...35 °C

Ambient air temperature for storage	−10...50 °C
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	8,0 cm
Pakendi laius 1	9,5 cm
Pakendi pikkus 1	9,5 cm
Pakendi kaal 1	158,0 g
Pakendi tüüp 2	S02
Ühikute arv pakendis 2	12
Pakendi kõrgus 2	15,0 cm
Pakendi laius 2	30,0 cm
Pakendi pikkus 2	40,0 cm
Pakendi kaal 2	2,134 kg
Pakendi tüüp 3	P12
Ühikute arv pakendis 3	384
Pakendi kõrgus 3	75,0 cm
Pakendi laius 3	80,0 cm
Pakendi pikkus 3	120,0 cm
Pakendi kaal 3	80,288 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	 REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus  ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	 Hiina RoHS Deklaratsioon
RoHS eranditeave	 Jah
Keskkonnavalade avaldus	 Toote Keskkonnaprofiil
Ringlusprofiil	 Kasutuselt Kõrvaldamise Teave
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.