

## Flashing light module; yellow; LED;24 V

**Part no.** **SL7-BL24-Y**  
**171388**  
**EL Number** **4137643**  
**(Norway)**

Product name	Eaton Moeller® series SL7 Flashing light module
Part no.	SL7-BL24-Y
EAN	4015081679232
Product Length/Depth	73 millimetre
Product height	73 millimetre
Product width	73 millimetre
Product weight	0.08 kilogram
Certifications	CSA-C22.2 No. 94-91 CSA-C22.2 No. 14-10 CSA Class No.: NKCR7 UL report applies to both US and Canada UL 508 Certified by UL for use in Canada UL File No.: E29184 UL Category Control No.: NKCR IEC/EN 60529 UL CE IEC/EN 60947-5-1
Product Tradename	SL7
Product Type	Flashing light module
Product Sub Type	None
Globally Marketable	Yes
Color	Yellow
Enclosure color	Black
Functions	Blinker light
Light modules	LED
Number of modules	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)
Connection to SmartWire-DT	No
Current consumption	0.058 A, at 24 V AC/DC
Degree of protection	IP66 NEMA 13
Flashing frequency	2 Hz
Lifespan, electrical	100,000 h
Light type	Flashing light
Material	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Type	Flashing light module
Voltage type	AC/DC
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C

Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Leakage current			0.003 A
Rated insulation voltage (Ui)			250 V
Rated operational voltage (Ue) at AC - min			24 V
Rated operational voltage (Ue) at AC - max			24 V
Rated operational voltage (Ue) at DC - min			24 V
Rated operational voltage (Ue) at DC - max			24 V

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])			
Function			Blinker light
Colour			Yellow
Outer diameter		mm	73
Operating voltage at AC 50 Hz		V	24 - 24
Operating voltage at AC 60 Hz		V	24 - 24
Operating voltage at DC		V	24 - 24
Voltage type			AC/DC
Lamp type			LED
Colour housing			Black
Degree of protection (IP)			IP66
Degree of protection (NEMA)			13