

Acoustic module;24 V;multi-tone

Part no. **SL7-AP24-M**
171287

EL Number **4137635**
(Norway)

Product name	Eaton Moeller® series SL7 Acoustic module
Part no.	SL7-AP24-M
EAN	4015081678327
Product Length/Depth	73 millimetre
Product height	71 millimetre
Product width	73 millimetre
Product weight	0.101 kilogram
Certifications	CE CSA-C22.2 No. 94-91 Certified by UL for use in Canada IEC/EN 60947-5-1 UL File No.: E29184 UL report applies to both US and Canada UL 508 UL Category Control No.: NKCR CSA Class No.: NKCR7 UL IEC/EN 60529 CSA-C22.2 No. 14-10
Product Tradename	SL7
Product Type	Acoustic module
Product Sub Type	None
Globally Marketable	Yes
Color	Black
Features	Sound pressure adjustable to a minimum of 88 dB
Functions	Other
Alarm type	Internal sound setting, 3 pole DIP Tone adjustable Pulsed tone 8 types of sound Continuous tone
Connection to SmartWire-DT	No
Current consumption	0.115 A, at 24 V AC/DC
Degree of protection	NEMA 13 IP66
Frequency rating	500 - 2700 Hz
Loudness	Can be adjusted with built-in potentiometer 100 dB
Material	Cap: Polycarbonate (PC) Enclosure: Polycarbonate (PC)
Mounting position	As required Place only at the highest position on a pole
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Type	Acoustic module
Voltage type	AC/DC
Ambient operating temperature - min	-30 °C

Ambient operating temperature - max			60 °C
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Leakage current			0.003 A
Rated insulation voltage (Ui)			250 V
Rated operational current (Ie) - max			115 A
Rated operational voltage (Ue) at AC - min			24 V
Rated operational voltage (Ue) at AC - max			24 V
Rated operational voltage (Ue) at DC - min			24 V
Rated operational voltage (Ue) at DC - max			24 V

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Acoustic module for signal tower (EC001261)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, acoustic (ecl@ss10.0.1-27-37-12-37 [AKF055014])			
Function			Other
Outer diameter		mm	73
Colour			Black
Operating voltage at AC 50 Hz		V	24 - 24
Operating voltage at AC 60 Hz		V	24 - 24
Operating voltage at DC		V	24 - 24
Voltage type			AC/DC
Tone adjustable			Yes
Degree of protection (IP)			IP66
Degree of protection (NEMA)			13
Loudness		dB	100