

Acoustic module;230 V;continuous or pulsed tone

Part no. SL7-AP230
171283
EL Number 4137631
(Norway)

Product name	Eaton Moeller® series SL7 Acoustic module
Part no.	SL7-AP230
EAN	4015081678129
Product Length/Depth	73 millimetre
Product height	71 millimetre
Product width	73 millimetre
Product weight	0.103 kilogram
Compliances	CE Marked
Certifications	UL Listed CSA Certified CSA Std. C22.2 No. 94-91 UL Listed file E29184 cULus Listed CSA Std. C22.2 No. 14-10 UL 508 CSA Class No. NKCR7 IEC Rated UL IEC/EN 60529 UL File No.: E29184 UL report applies to both US and Canada UL Category Control No.: NKCR CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 CSA Class No.: NKCR7 CE IEC/EN 60947-5-1 Certified by UL for use in Canada
Product Tradename	SL7
Product Type	Acoustic module
Product Sub Type	None
Globally Marketable	Yes
Color	Black
Features	Sound pressure adjustable to a minimum of 88 dB
Functions	Continuous tone/pulse tone
Accessories	Internal DIP switch, internal potentiometer
Alarm type	Pulsed tone Tone adjustable 2 types of sound Continuous tone Internal sound setting, 1 pole DIP
Connection to SmartWire-DT	No
Current consumption	0.043 A, at 230/240 V AC
Degree of protection	NEMA 13 IP66
Frequency rating	2800 Hz
Loudness	Can be adjusted with built-in potentiometer 100 dB
Material	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
Mounting position	Place only at the highest position on a pole As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °

Rated impulse withstand voltage (Uimp)		4000 V AC
Shock resistance		15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Type		Acoustic module
Voltage type		AC
Ambient operating temperature - min		-30 °C
Ambient operating temperature - max		60 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Leakage current		0.003 A
Rated insulation voltage (Ui)		250 V
Rated operational current (Ie) - max		43 A
Rated operational voltage (Ue) at AC - min		230 V
Rated operational voltage (Ue) at AC - max		240 V
Rated operational voltage (Ue) at DC - min		0 V
Rated operational voltage (Ue) at DC - max		0 V

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Acoustic module for signal tower (EC001261)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, acoustic (ecl@ss10.0.1-27-37-12-37 [AKF055014])		
Function		Continuous tone/pulse tone
Outer diameter	mm	73
Colour		Black
Operating voltage at AC 50 Hz	V	230 - 240
Operating voltage at AC 60 Hz	V	230 - 240
Operating voltage at DC	V	0 - 0
Voltage type		AC
Tone adjustable		Yes
Degree of protection (IP)		IP66
Degree of protection (NEMA)		13
Loudness	dB	100