

PRODUCT-DETAILS

AF65-30-00-13

AF65-30-00-13 100-250V50/60HZ-DC Contactor



General Information

| | |
|-----------------------|--|
| Extended Product Type | AF65-30-00-13 |
| Product ID | 1SBL387001R1300 |
| EAN | 3471523132634 |
| Catalog Description | AF65-30-00-13 100-250V50/60HZ-DC Contactor |

Long Description

The AF65-30-00-13 is a 3 pole - 690 V IEC or 600 UL contactor with screw terminals, controlling motors up to 30 kW / 400 V AC (AC-3) or 50 hp / 480 V UL and switching power circuits up to 105 A (AC-1) or 90 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101036M6801 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 55 mm |
| Product Net Depth / Length | 111 mm |
| Product Net Height | 125.5 mm |
| Product Net Weight | 0.95 kg |

Technical

| | |
|---|---|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Number of Auxiliary Contacts NC | 0 |
| Rated Operational Voltage | Main Circuit 690 V |
| Rated Frequency (f) | Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current (I_{th}) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 105 A |
| Rated Operational Current AC-1 (I_e) | (690 V) 40 °C 105 A (690 V) 60 °C 90 A (690 V) 70 °C 80 A |
| Rated Operational Current AC-3 (I_e) | (415 V) 60 °C 65 A (440 V) 60 °C 65 A (500 V) 60 °C 55 A (690 V) 60 °C 39 A (380 / 400 V) 60 °C 65 A (220 / 230 / 240 V) 60 °C 65 A |
| Rated Operational Current AC-3e (I_e) | (415 V) 60 °C 65 A (440 V) 60 °C 65 A (500 V) 60 °C 55 A (690 V) 60 °C 39 A (380 / 400 V) 60 °C 65 A (220 / 230 / 240 V) 60 °C 65 A |
| Rated Operational Power AC-3 (P_e) | (400 V) 30 kW (415 V) 37 kW (440 V) 37 kW (500 V) 37 kW (690 V) 37 kW (380 / 400 V) 30 kW (220 / 230 / 240 V) 18.5 kW |
| Rated Operational Power AC-3e (P_e) | (415 V) 37 kW (440 V) 37 kW (500 V) 37 kW (690 V) 37 kW (380 / 400 V) 30 kW (220 / 230 / 240 V) 18.5 kW |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 350 A |
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for $I_e > 100\text{ A}$) at 440 V 950 A cos phi=0.45 (cos phi=0.35 for $I_e > 100\text{ A}$) at 690 V 600 A |
| Maximum Electrical Switching Frequency | (AC-1) 600 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 1200 cycles per hour |
| Rated Operational Current DC-1 (I_e) | (110 V) 2 Poles in Series, 40 °C 105 A (110 V) 2 Poles in Series, 60 °C 90 A (110 V) 2 Poles in Series, 70 °C 80 A (110 V) 3 Poles in Series, 40 °C 105 A (110 V) 3 Poles in Series, 60 °C 90 A |

| | |
|--|--|
| | (110 V) 3 Poles in Series, 70 °C 80 A (220 V) 3 Poles in Series, 40 °C 105 A (220 V) 3 Poles in Series, 60 °C 90 A (220 V) 3 Poles in Series, 70 °C 80 A (72 V) 1-Pole, 40 °C 105 A (72 V) 1-Pole, 60 °C 90 A (72 V) 1-Pole, 70 °C 80 A (72 V) 2 Poles in Series, 40 °C 105 A (72 V) 2 Poles in Series, 60 °C 90 A (72 V) 2 Poles in Series, 70 °C 80 A (72 V) 3 Poles in Series, 40 °C 105 A (72 V) 3 Poles in Series, 60 °C 90 A (72 V) 3 Poles in Series, 70 °C 80 A |
| Rated Operational Current DC-3 (I_e) | (110 V) 2 Poles in Series, 40 °C 105 A (110 V) 2 Poles in Series, 60 °C 90 A (110 V) 2 Poles in Series, 70 °C 80 A (110 V) 3 Poles in Series, 40 °C 105 A (110 V) 3 Poles in Series, 60 °C 90 A (110 V) 3 Poles in Series, 70 °C 80 A (220 V) 3 Poles in Series, 40 °C 105 A (220 V) 3 Poles in Series, 60 °C 90 A (220 V) 3 Poles in Series, 70 °C 80 A (72 V) 1-Pole, 40 °C 105 A (72 V) 1-Pole, 60 °C 90 A (72 V) 1-Pole, 70 °C 80 A (72 V) 2 Poles in Series, 40 °C 105 A (72 V) 2 Poles in Series, 60 °C 90 A (72 V) 2 Poles in Series, 70 °C 80 A (72 V) 3 Poles in Series, 40 °C 105 A (72 V) 3 Poles in Series, 60 °C 90 A (72 V) 3 Poles in Series, 70 °C 80 A |
| Rated Operational Current DC-5 (I_e) | (110 V) 2 Poles in Series, 40 °C 105 A (110 V) 2 Poles in Series, 60 °C 90 A (110 V) 2 Poles in Series, 70 °C 80 A (110 V) 3 Poles in Series, 40 °C 105 A (110 V) 3 Poles in Series, 60 °C 90 A (110 V) 3 Poles in Series, 70 °C 80 A (220 V) 3 Poles in Series, 40 °C 105 A (220 V) 3 Poles in Series, 60 °C 90 A (220 V) 3 Poles in Series, 70 °C 80 A (72 V) 1-Pole, 40 °C 105 A (72 V) 1-Pole, 60 °C 90 A (72 V) 1-Pole, 70 °C 80 A (72 V) 2 Poles in Series, 40 °C 105 A (72 V) 2 Poles in Series, 60 °C 90 A (72 V) 2 Poles in Series, 70 °C 80 A (72 V) 3 Poles in Series, 40 °C 105 A (72 V) 3 Poles in Series, 60 °C 90 A (72 V) 3 Poles in Series, 70 °C 80 A |
| Rated Insulation Voltage (U_i) | acc. to IEC 60947-4-1 690 V acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 6 kV |
| Maximum Mechanical Switching Frequency | 3600 cycles per hour |
| Rated Control Circuit Voltage (U_c) | 50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V |
| Operate Time | Between Coil De-energization and NC Contact Closing 19 ... 105 ms Between Coil De-energization and NO Contact Opening 17 ... 100 ms Between Coil Energization and NC Contact Opening 38 ... 95 ms Between Coil Energization and NO Contact Closing 42 ... 100 ms |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting by Screws (not supplied) | 2 x M4 or 2 x M6 screws placed diagonally |
| Connecting Capacity Main Circuit | Flexible with Ferrule 1/2x 4 ... 35 mm ² Flexible with Insulated Ferrule 1/2x 4 ... 35 mm ² Rigid Stranded 1/2x 6 ... 35 mm ² |
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ² |
| Wire Stripping Length | Control Circuit 10 mm |

| | |
|----------------------|--|
| | Main Circuit 16 mm |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10 |
| Terminal Type | Screw Terminals |

Technical UL/CSA

| | |
|---|---|
| General Use Rating UL/CSA | (600 V AC) 90 A |
| Horsepower Rating UL/CSA | (120 V AC) Single Phase 5 hp (200 ... 208 V AC) Three Phase 20 hp (220 ... 240 V AC) Three Phase 25 hp (240 V AC) Single Phase 15 hp (440 ... 480 V AC) Three Phase 50 hp (550 ... 600 V AC) Three Phase 60 hp |
| Connecting Capacity Main Circuit UL/CSA | Rigid Stranded 1/2x 10-2 AWG |
| Connecting Capacity Control Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG |
| Tightening Torque UL/CSA | Control Circuit 11 in-lb Main Circuit 35 in-lb |

Environmental

| | |
|---|--|
| Ambient Air Temperature | Close to Contactor Fitted with Thermal O/L Relay -40 ... 70 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand | Category B according to IEC 60947-1 Annex Q |
| Maximum Operating Altitude Permissible | Without Derating 3000 m |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5 ... 300 Hz 3 g closed position / 3 g open position |
| Resistance to Shock acc. to IEC 60068-2-27 | Closed, Shock Direction: A 25 g Closed, Shock Direction: B1 25 g Closed, Shock Direction: B2 15 g Closed, Shock Direction: C1 25 g Closed, Shock Direction: C2 25 g Open, Shock Direction: B1 5 g |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|-------------------------------------|--|
| ABS Certificate | ABS_20-2060694-PDA |
| BV Certificate | BV_2634H36994B1 |
| CB Certificate | CB_SE-108889A1 |
| CCC Certificate | CCC_2012010304589737 CCC_2015010304824714 |
| CQC Certificate | CQC2015010304824714 CQC2012010304589737 |
| Declaration of Conformity - CCC | 2020980304001256 2020980304001074 |
| Declaration of Conformity - CE | 1SBD250000U1000 |
| Declaration of Conformity - UKCA | 1SBD250031U1000 |
| EAC Certificate | EAC_RU_FRME77B03447 |
| Environmental Information | 1SBD250168E1000 1SBC100222M0201 |
| GL Certificate | DNV-GL_TAE00001AF-3 |
| Instructions and Manuals | 1SBC101036M6801 |

| | |
|-------------------|--------------------------|
| KC Certificate | KC_HW02016-15003C |
| LR Certificate | LRS_1300087E1 |
| REACH Declaration | 2CMT2021-006202 |
| RINA Certificate | RINA_ELE084013XG |
| RMRS Certificate | RMRS_1802705280 |
| RoHS Information | 2CMT2021-006277 |
| UL Certificate | UL_20130301_E312527_14_1 |
| UL Listing Card | UL_E312527 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 150 mm |
| Package Level 1 Depth / Length | 150 mm |
| Package Level 1 Height | 97 mm |
| Package Level 1 Gross Weight | 1.05 kg |
| Package Level 1 EAN | 3471523132634 |
| Package Level 2 Units | box 10 piece |
| Package Level 2 Width | 250 mm |
| Package Level 2 Depth / Length | 300 mm |
| Package Level 2 Height | 300 mm |
| Package Level 2 Gross Weight | 10.5 kg |
| Package Level 3 Units | 240 piece |

Classifications

| | |
|------------------------------------|---|
| Object Classification Code | Q |
| ETIM 4 | EC000066 - Magnet contactor, AC-switching |
| ETIM 5 | EC000066 - Magnet contactor, AC-switching |
| ETIM 6 | EC000066 - Power contactor, AC switching |
| ETIM 7 | EC000066 - Power contactor, AC switching |
| ETIM 8 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |
| IDEA Granular Category Code (IGCC) | 4758 >> lec Contactors |
| E-Number (Finland) | 3707048 |
| E-Number (Sweden) | 3210045 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

