

Toote infoleht

Tehnilised andmed



Easy9 - flush enclosure 24 modules - plain door - with E/N term.blocks

EZ9E212P2F

! Tootmine lõpetatud: 10 oktoober 2022

! Teeninduse lõpp: 01 jaanuar 2023

! Tootmisest maas

Main

Range	Easy9
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	12

Complementary

Enclosure mounting	Flush
9 mm pitches	24
Nb of horizontal rows	2
Total number of 18 mm modules	24
Type of rail	DIN
Type of installation	Indoor
Terminal block function	Earth / neutral
Number of terminal blocks	2 earth / neutral screwed)17
Cable entry	Tube entry
Type of door	Plain door
Door opening side	Reversible 180 °)
[In] rated current	63 A
[Ue] rated operational voltage	400 V AC
[Uimp] rated impulse withstand voltage	2,5 kV
[Ui] rated insulation voltage	500 V
Enclosure material	Enclosure self-extinguishing plastic
Width	Outside 300 mm
Height	Outside 345 mm
Depth	Outside 100 mm
Colour	white RAL 9003)
Product weight	1380 g

Environment

Standards	IEC 60670-1-24
Fire resistance	650 °C 1800 s) IEC 60695-2-10
IP degree of protection	IP40 IEC 60529 closed door) IP30 IEC 60529 open door)
IK degree of protection	IK07 IEC 62262
Pollution degree	2
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-15...70 °C

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	10 cm
Pakendi laius 1	30 cm
Pakendi pikkus 1	34,5 cm
Pakendi kaal 1	1,269 kg

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Ennetav vastavus (toode ei jää EL-i RoHS seadustega määratud piiridesse) ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.
RoHS eranditeave	Jah
Halogeensisu	Halogeenivaba toode

Soovitatud asendus(ed)