

Contactors, 3 pole, 380 V 400 V 5.5 kW, 1 N/O, 24 V 50 Hz, AC operation, Screw terminals



Part no. DILM12-10(24V50HZ)

276817

**EL Number
(Norway)**

4130318

| | |
|--|--|
| Product name | Eaton Moeller® series DILM contactor |
| Part no. | DILM12-10(24V50HZ) |
| EAN | 4015082768171 |
| Product Length/Depth | 75 millimetre |
| Product height | 68 millimetre |
| Product width | 45 millimetre |
| Product weight | 0.24 kilogram |
| Compliances | CE Marked |
| Certifications | CSA Std. C22.2 No. 14-05 IEC 60947-4-1 EN 60947-4-1 UL 508 VDE UL File No.: E29096 VDE 0660 CSA Class No.: 2411-03, 3211-04 CSA File No.: 012528 UL 60947-4-1 CSA UL CE UL Category Control No.: NLDX IEC/EN 60947-4-1 IEC/EN 60947 CSA-C22.2 No. 60947-4-1-14 |
| Product Tradename | DILM |
| Product Type | Contactors |
| Product Sub Type | None |
| Catalog Notes | Contacts according to EN 50012 |
| Application | Contactors for Motors |
| Degree of protection | IP20 |
| Frame size | FS1 |
| Lifespan, mechanical | 10,000,000 Operations (AC operated) |
| Operating frequency | 9000 mechanical Operations/h (AC operated) |
| Overvoltage category | III |
| Pollution degree | 3 |
| Product category | Contactors |
| Protection | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) |
| Rated impulse withstand voltage (Uimp) | 8000 V AC |
| Resistance per pole | 2.5 mΩ |
| Suitable for | Also motors with efficiency class IE3 |
| Utilization category | AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| Voltage type | AC |
| Shock resistance | 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 3.4 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 5.7 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms |

| | | |
|---|--|---|
| | | 3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms |
| Altitude | | Max. 2000 m |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 60 °C |
| Ambient operating temperature (enclosed) - min | | 25 °C |
| Ambient operating temperature (enclosed) - max | | 40 °C |
| Ambient storage temperature - min | | 40 °C |
| Ambient storage temperature - max | | 80 °C |
| Climatic proofing | | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| Emitted interference | | According to EN 60947-1 |
| Interference immunity | | According to EN 60947-1 |
| Terminal capacity (flexible with ferrule) | | 1 x (0.75 - 2.5) mm ² 2 x (0.75 - 2.5) mm ² 2 x (0.75 - 2.5) mm ² |
| Terminal capacity (solid) | | 2 x (0.75 - 2.5) mm ² 1 x (0.75 - 4) mm ² |
| Terminal capacity (solid/stranded AWG) | | Single 18 - 10, double 18 - 14 |
| Stripping length (main cable) | | 10 mm |
| Stripping length (control circuit cable) | | 10 mm |
| Screw size | | M3.5, Terminal screw |
| Screwdriver size | | 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver |
| Tightening torque | | 1.2 Nm, Screw terminals |
| Rated breaking capacity at 220/230 V | | 120 A |
| Rated breaking capacity at 380/400 V | | 120 A |
| Rated breaking capacity at 500 V | | 100 A |
| Rated breaking capacity at 660/690 V | | 70 A |
| Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V | | 22 A |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | | 12 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | | 12 A |
| Rated operational current (Ie) at AC-3, 440 V | | 12 A |
| Rated operational current (Ie) at AC-3, 500 V | | 10 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | | 7 A |
| Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V | | 7 A |
| Rated operational current (Ie) at AC-4, 440 V | | 7 A |
| Rated operational current (Ie) at AC-4, 500 V | | 6 A |
| Rated operational current (Ie) at AC-4, 660 V, 690 V | | 5 A |
| Rated operational current (Ie) at DC-1, 60 V | | 20 A |
| Rated operational current (Ie) at DC-1, 110 V | | 20 A |
| Rated operational current (Ie) at DC-1, 220 V | | 15 A |
| Rated insulation voltage (Ui) | | 690 V |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947) | | 144 A |
| Rated operational power at AC-3, 240 V, 50 Hz | | 4 kW |
| Rated operational power at AC-3, 380/400 V, 50 Hz | | 5.5 kW |
| Rated operational power at AC-3, 415 V, 50 Hz | | 7 kW |
| Rated operational power at AC-3, 440 V, 50 Hz | | 7.5 kW |
| Rated operational power at AC-3, 500 V, 50 Hz | | 7 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | | 6.5 kW |
| Rated operational power at AC-4, 220/230 V, 50 Hz | | 2 kW |
| Rated operational power at AC-4, 240 V, 50 Hz | | 2.2 kW |
| Rated operational power at AC-4, 415 V, 50 Hz | | 3.4 kW |
| Rated operational power at AC-4, 440 V, 50 Hz | | 3.6 kW |

| | | |
|---|--|---|
| Rated operational power at AC-4, 500 V, 50 Hz | | 3.5 kW |
| Rated operational power at AC-4, 660/690 V, 50 Hz | | 4.4 kW |
| Rated operational voltage (Ue) at AC - max | | 690 V |
| Short-circuit current rating (basic rating) | | 45 A, max. Fuse, SCCR (UL/CSA) 60 A, max. CB, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) |
| Short-circuit current rating (high fault at 480 V) | | 25 A, Class RK5/ 45 A Class J, max. Fuse, SCCR (UL/CSA) 30/100 kA, Fuse, SCCR (UL/CSA) |
| Short-circuit current rating (high fault at 600 V) | | 30/100 kA, Fuse, SCCR (UL/CSA) 25 A, Class RK5/45 A, Class J, max. Fuse, SCCR (UL/CSA) |
| Short-circuit protection rating (type 1 coordination) at 400 V | | 35 A gG/gL |
| Short-circuit protection rating (type 1 coordination) at 690 V | | 25 A gG/gL |
| Short-circuit protection rating (type 2 coordination) at 400 V | | 20 A gG/gL |
| Short-circuit protection rating (type 2 coordination) at 690 V | | 20 A gG/gL |
| Conventional thermal current I_{th} (1-pole, enclosed) | | 45 A |
| Conventional thermal current I_{th} (3-pole, enclosed) | | 18 A |
| Conventional thermal current I_{th} at 55°C (3-pole, open) | | 21 A |
| Conventional thermal current I_{th} at 60°C (3-pole, open) | | 20 A |
| Conventional thermal current I_{th} of main contacts (1-pole, open) | | 50 A |
| Switching capacity (main contacts, general use) | | 20 A, Maximum motor rating (UL/CSA) |
| Switching capacity (auxiliary contacts, general use) | | 10 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | | A600, AC operated (UL/CSA) P300, DC operated (UL/CSA) |
| Arcing time | | 10 ms |
| Drop-out voltage | | AC operated: 0.6 - 0.3 x U _C , AC operated |
| Duty factor | | 100 % |
| Pick-up voltage | | 0.8 - 1.1 V AC x U _C |
| Power consumption, pick-up, 50 Hz | | 24 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz |
| Power consumption, pick-up, 60 Hz | | 30 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz |
| Power consumption, sealing, 50 Hz | | 3.4 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz 1.4 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 50 Hz |
| Power consumption, sealing, 60 Hz | | 1.4 W, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz 4.4 VA, Dual-frequency coil in a cold state and 1.0 x U _s , at 60 Hz |
| Rated control supply voltage (U _s) at AC, 50 Hz - min | | 24 V |
| Rated control supply voltage (U _s) at AC, 50 Hz - max | | 24 V |
| Rated control supply voltage (U _s) at AC, 60 Hz - min | | 0 V |
| Rated control supply voltage (U _s) at AC, 60 Hz - max | | 0 V |
| Rated control supply voltage (U _s) at DC - min | | 0 V |
| Rated control supply voltage (U _s) at DC - max | | 0 V |
| Switching time (AC operated, make contacts, closing delay) - min | | 15 ms |
| Switching time (AC operated, make contacts, closing delay) - max | | 21 ms |
| Switching time (AC operated, make contacts, opening delay) - min | | 9 ms |
| Switching time (AC operated, make contacts, opening delay) - max | | 18 ms |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase | | 1 HP |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase | | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | | 2 HP |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase | | 3 HP |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase | | 10 HP |
| Assigned motor power at 575/600 V, 60 Hz, 3-phase | | 10 HP |
| Connection | | Screw terminals |
| Connection to SmartWire-DT | | No |

| | | |
|--|--|---|
| Number of contacts (normally open contacts) | | 1 |
| Number of auxiliary contacts (normally closed contacts) | | 0 |
| Number of auxiliary contacts (normally open contacts) | | 1 |
| Safe isolation | | 400 V AC, Between the contacts, According to EN 61140 400 V AC, Between coil and contacts, According to EN 61140 |
| Special purpose rating of ballast electrical discharge lamps | | 20 A (600V 60Hz 3phase, 347V 60Hz 1phase) 20 A (480V 60Hz 3phase, 277V 60Hz 1phase) |
| Special purpose rating of definite purpose rating | | 72 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 12 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) |
| Special purpose rating of elevator control | | 2 HP, 200 V 60 Hz 3-ph, (UL/CSA) 9 A, 600 V 60 Hz 3-ph, (UL/CSA) 7.5 HP, 480 V 60 Hz 3-ph, (UL/CSA) 6.8 A, 240 V 60 Hz 3-ph, (UL/CSA) 7.5 HP, 600 V 60 Hz 3-ph, (UL/CSA) 11 A, 480 V 60 Hz 3-ph, (UL/CSA) 7.8 A, 200 V 60 Hz 3-ph, (UL/CSA) 2 HP, 240 V 60 Hz 3-ph, (UL/CSA) |
| Special purpose rating of refrigeration control (CSA only) | | 10 A, FLA 480 V 60 Hz 3phase; (CSA) 60 A, LRA 600 V 60 Hz 3phase; (CSA) 60 A, LRA 480 V 60 Hz 3phase; (CSA) 10 A, FLA 600 V 60 Hz 3phase; (CSA) |
| Special purpose rating of resistance air heating | | 20 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 20 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) |
| Special purpose rating of tungsten incandescent lamps | | 14 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 14 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0.3 W |
| Rated operational current for specified heat dissipation (I _n) | | 12 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 1.4 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

| | | |
|---|---|---------|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015]) | | |
| Rated control supply voltage U _s at AC 50HZ | V | 24 - 24 |

| | | |
|---|----|------------------|
| Rated control supply voltage Us at AC 60HZ | V | 0 - 0 |
| Rated control supply voltage Us at DC | V | 0 - 0 |
| Voltage type for actuating | | AC |
| Rated operation current Ie at AC-1, 400 V | A | 22 |
| Rated operation current Ie at AC-3, 400 V | A | 12 |
| Rated operation power at AC-3, 400 V | kW | 5.5 |
| Rated operation current Ie at AC-4, 400 V | A | 7 |
| Rated operation power at AC-4, 400 V | kW | 3 |
| Rated operation power NEMA | kW | 7.4 |
| Modular version | | No |
| Number of auxiliary contacts as normally open contact | | 1 |
| Number of auxiliary contacts as normally closed contact | | 0 |
| Type of electrical connection of main circuit | | Screw connection |
| Number of normally closed contacts as main contact | | 0 |
| Number of normally open contacts as main contact | | 3 |