

**Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40...-  
ASA...IHK...WHK, Z-MS, 1N/O+1N/C, 0.5HP**



**Part no.**                    **ZP-IHK**  
**286052**  
**EL Number**                **1609488**  
**(Norway)**

Product name	Eaton Distribution parts
Part no.	ZP-IHK
EAN	4015082860523
Product Length/Depth	80 millimetre
Product height	75 millimetre
Product width	8.8 millimetre
Product weight	0.043 kilogram
Compliances	RoHS conform
Certifications	IEC 61373 EN45545-2
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes
Accessory/spare part type	Auxiliary contacts
Additional equipment required	Auxiliary switch
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for industrial and advanced commercial applications
Assembly width	0.5
Device fitting	Universal
EL number	1609488
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	2
Number of switches (fault signal)	0
Rated operational voltage (Ue) - max	230 V
Rated switch current	3 A
Suitable for current of main contact unit - max	6 A
Type	Accessory Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker
Used with	Auxiliary contacts Accessory for combined residual current/power circuit breaker Accessory for miniature circuit breaker Accessory
Voltage type	AC

## Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Universal
Additional equipment		Auxiliary switch
Installed at the factory		No

Width in number of modular spacings			0.5
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	3
Rated voltage		V	230
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			2
Suitable for max. current main contact unit		A	6