



VU36NE

Encl.,Volta,flush,3x12MOD,IP30,Version NCEE

Technical properties

Architecture

| | |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

Functions

| | |
|---------------------|-----|
| With a pipe-in lead | Yes |
|---------------------|-----|

Configuration

| | |
|-------------------|----|
| Number of modules | 36 |
|-------------------|----|

Main electrical features

| | |
|-----------------|-------|
| Nominal voltage | 400 V |
|-----------------|-------|

Electric current

| | |
|---------------|------|
| Rated current | 63 A |
|---------------|------|

Dimensions

| | |
|--------------------------------|----------|
| Insertion depth | 89 mm |
| Depth of installed product | 98 mm |
| Internal depth | 91.5 mm |
| Height of installed product | 630.5 mm |
| Installation height | 595 mm |
| Length | 630.5 mm |
| Width of installed product | 348 mm |
| Width in division units | 12 |
| Thickness of sidewall material | 2.5 mm |
| Built-in height | 615 mm |
| Built-in width | 314.5 mm |

Cover, door

| | |
|------------------------------------|------------|
| Type of door closing | Latch |
| Identification of protection index | 30 |
| Interlockable | No |
| Number of keylock of the door | 0 |
| Cover type | With Notch |
| Door locking | without |
| Door leave | single |
| Cover type | Door |
| Transparent cover or door | No |

Materials

| | |
|---|--|
| Colour | pure white |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | plastic |
| Type of surface treatment | untreated |
| Installation, mounting | |
| Suitable for outdoor use | No |
| Settings | |
| Enclosure type | Distributor empty cabinet |
| Scope of delivery | |
| With cover | No |
| Equipment | |
| Number of units | 12 |
| Number of rows | 3 |
| Quantity of rails | 3 |
| Can be accessorized | Yes |
| Number of openings for flange plates | 0 |
| Extension possible | Yes |
| Earthing terminal block | Yes |
| Neutral terminal block | No |
| Signal passing door | No |
| Standards | |
| GWT Glow wire test | 650 °C |
| European directive WEEE | concerned |
| Protection class according to IEC-61140 | II |
| Safety | |
| IK protection code against mechanical impacts | IK07 |
| Protection index IP | IP30 |
| Protection class | isol.class II |
| Halogen free | Yes |
| Impact strength | IK05 |
| Use conditions | |
| Operating temperature | -40...40 °C |
| Identification | |
| meta_keyword | Volta distribution board;distributor;distribution board;flush-mounted;sheet metal door |