

PRODUCT-DETAILS

# DS201 B10 AC30

## DS201 B10 AC30 Residual Current Circuit Breaker with Overcurrent Protection



### General Information

Extended Product Type	DS201 B10 AC30
Product ID	2CSR255080R1105
EAN	8012542333913
Catalog Description	DS201 B10 AC30 Residual Current Circuit Breaker with Overcurrent Protection
Long Description	The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

### Technical

Standards	IEC/EN 61009-1, IEC/EN 61009-2-1
Tripping Characteristic	B
Type of Residual Current	AC type
Rated Voltage ( $U_r$ )	230 V
Rated Operational Voltage	230 / 240 V AC
Rated Insulation Voltage ( $U_i$ )	500 V
Test Voltage ( $U_t$ )	170 ... 264 V
Dielectric Test Voltage	2 kV
Primary Rated Impulse Withstand Voltage	4 kV

Input Voltage Type	AC
Rated Current ( $I_n$ )	10 A
Rated Residual Current	30 mA
Rated Short-Circuit Capacity	6 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	10 kA
Rated Residual Breaking Capacity ( $I_{\Delta m}$ )	EN 61009-1 6000 A IEC 61009-1 6000 A
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	10 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	7.5 kA
Maximum Surge Current	0 kA
Leakage Current Type	AC
Frequency (f)	50/60 Hz
Rated Frequency (f)	50 ... 60 Hz
Power Loss	Average per Pole 1,2 W Phase Pole 1,8 W Neutral Pole 0,5 W Total 2,3 W
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Poles	2
Number of Protected Poles	1
Number of Modular Spacings per DIN Rail	2
Fault Indication	Blue flag on toggle
Operating Characteristic	Instantaneous
Overvoltage Category	III
Position of Neutral Terminals	Right
Tightening Torque	2.8 N·m
Accessory Type	Auxiliary contact, Signal contact / auxiliary contact, Shunt trip, Auxiliary contact for bottom fitting, Overvoltage release, Motor operating device
Actuator Type	Toggle - Insulation group II, Black RAL 9005, sealable in ON-OFF positions
Housing Type	Insulation group I - II, RAL 7035
Mounting Type	DIN-Rail
Release Type	B
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Mounting Position	Any
Accessories Available	Yes
Number of Batteries	0
Cable Size	25 mm <sup>2</sup>
Connecting Capacity	Busbar 10 ... 10 mm <sup>2</sup> Stranded 0.75 ... 25 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 16 mm <sup>2</sup> Flexible 0.75 ... 16 mm <sup>2</sup>
Wire Stripping Length	12 mm
Terminal Type	Screw Terminals

---

**Environmental**


---

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25...55 °C
Reference Ambient Air Temperature	30 °C
Degree of Protection	Terminals IP20 Housing IP40
Pollution Degree	2
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations acc. to IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 5...150..5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK106713A5588
REACH Declaration	9AKK108467A9482
Environmental Information	2CSC422002K2701
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

---



---

**Dimensions**


---

Width in Number of Modular Spacings	2
Product Net Width	0.035 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.200 kg
Built-In Depth (t <sub>2</sub> )	69 mm

---



---

**Ordering**


---

Minimum Order Quantity	1 piece
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	225 g

---



---

**Certificates and Declarations**


---

ABS Certificate	9AKK107991A2823
CB Certificate	9AKK107492A6060
CCC Certificate	9AKK107492A6067
Declaration of Conformity - CE	9AKK106713A5588
DNV GL Certificate	9AKK107680A3457 9AKK107680A3456
EAC Certificate	9AKK107492A6071 9AKK107991A7755
GOST Certificate	9AKK107992A1640
ÖVE Certificate	9AKK107492A6085

---

RMRS Certificate

9AKK107680A3454  
9AKK107680A3455

---

**Installation**

---

Instructions and Manuals

9AKK107492A6006

---

---

**Popular Downloads**

---

Data Sheet, Technical  
Information9AKK107492A6187

---

EPLAN Macro

9AKK107680A0597

---

---

**Classifications**

---

ETIM 8

EC000905 - Earth leakage circuit breaker

ETIM 9

EC000905 - Earth leakage circuit breaker

EPLAN Catalog Tree

Electrical engineering / Protection devices / Ground fault current circuit breaker

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B

Business To Consumer

CN8

85363010

eClass

V11.0 : 27142207

---

Object Classification Code

F

---

---

**Accessories**

---

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200970R0031	S2C-H01 Auxiliary Contact	S2C-H01	1	piece
2CDS200970R0032	S2C-H10 Auxiliary Contact	S2C-H10	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage release	S2C-OVP1	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage release	S2C-OVP2	1	piece
2CSS203997R0013	S2C-CM2/3 Motor operating device	S2C-CM2/3	1	piece

---

**Categories**

---

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

