

PRODUCT-DETAILS

## FH204 AC-25/0.03 FH204 AC-25/0.03 Residual Current Circuit Breaker 4P AC type 30 mA



General Information	
Extended Product Type	FH204 AC-25/0.03
Product ID	2CSF204004R1250
EAN	8012542893905
Catalog Description	FH204 AC-25/0.03 Residual Current Circuit Breaker 4P AC type 30 mA
Long Description	The RCCBs FH200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous AC and A types is particularly suitable for installation in domestic applications.

Technical	
Standards	IEC/EN 61008
Type of Residual Current	AC type
Rated Voltage (U <sub>r</sub> )	230/400 V
Rated Operational Voltage	230 / 400 V AC
Rated Insulation Voltage $(U_i)$	500 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Rated Current (I <sub>n</sub> )	25 A
Rated Residual Current	30 mA
Rated Service Short- Circuit Breaking Capacity (I <sub>cs</sub> )	1 kA
Maximum Surge Current	0.25 kA
Leakage Current Type	AC

Rated Frequency (f)	50 Hz
Power Loss	at Rated Operating Conditions per Pole 1.3 W
Number of Poles	4
Operating Characteristic	Instantaneous
Position of Neutral Terminals	Right
Mounting Type	DIN-Rail
Options Provided	None
Accessories Available	No
Rated Cross-Section	4 - Multi-Wired 1025 mm² 1 - Solid-Core 2525 mm²

Environmental	
Ambient Air Temperature	Operation -5 +40 °C Storage -40 +70 °C
Degree of Protection	IP2X
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK106713A5603
REACH Declaration	9AKK108467A9482
Environmental Information	Refer to RoHS
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Technical UL/CSA	
Short-Circuit Current Rating (SCCR)	0.03 A
Dimensione	
Dimensions	
Width in Number of Modular Spacings	4

Modulai Spacings	
Product Net Width	70 mm
Product Net Height	69 mm
Product Net Depth / Length	85 mm
Product Net Weight	0.38 kg
Built-In Depth (t <sub>2</sub> )	69 mm

Ordering	
Minimum Order Quantity	1 piece
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.415 kg

9AKK106713A5603

Installation

Instructions and Manuals

No document needed

Popular Downloads	
Data Sheet, Technical Information	2CSC400030D0202

Classifications	
ETIM 8	EC000003 - Residual current circuit breaker (RCCB)
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
<u>CN8</u>	85363030
eClass	V11.0 : 27142201
Object Classification Code	<u> </u>

Categories

 ${\sf Low \ Voltage \ Products \ and \ Systems \ \rightarrow \ Modular \ DIN \ Rail \ Products \ \rightarrow \ Residual \ Current \ Devices \ RCDs \ \rightarrow \ Residual \ Current \ Devices \ RCDs \ and \ Systems \ Add \ Residual \ Current \ Devices \ RCDs \ and \ Residual \ Current \ Devices \ RCDs \ and \ Residual \ Current \ Devices \ RCDs \ and \ Residual \ Current \ Devices \ RCDs \ and \ Residual \ Current \ Devices \ RCDs \ and \ Residual \ Residu$ 





