

TYPE APPROVAL CERTIFICATE

Certificate No: **TAE00000SV** Revision No: **1**

This is to certify:

That the Electric Power Cable

with type designation(s)

LM-HF 0,6/1 kV or TEMAR PHFX-U 0,6/1 kV

Issued to

Prysmian Group Finland Oy PIKKALA, Finland

is found to comply with

DNV GL rules for classification - Ships, offshore units, and high speed and light craft

Application:

General power and lighting. Control.

Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.

Rated voltage (kV) 0,6/1 Temp. class (°C) 90

This Certificate is valid until 2025-06-30.

Issued at **Høvik** on **2020-09-17**DNV GL local station: **Helsinki FIS**

for **DNV GL**

Approval Engineer: Ivar Bull

Marta Alonso Pontes Head of Section

Form code: TA 1411a Revision: 2015-05 www.dnvgl.com Page 1 of 3

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-011072-3** Certificate No: **TAE00000SV**

Revision No: 1

Product description

Type: LM-HF 0,6/1 kV or TEMAR PHFX-U 0,6/1 kV

Construction:

Conductors: Plain stranded copper class 2 or class 5

Insulation: XLPE

Inner covering: Possible extruded in multicore class 5 cables (not for single core cables)

Outer sheath: SHF1

Class 2:

No of cores	Cross sectional area [mm ²]			
1	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300			
2	1.5, 2.5, 4, 6			
3	1.5, 2.5, 4, 6, 10, 16, 25, 35*, 50*, 70*, 95*, 120*, 150*, 185*, 240*, 300*			
4	1.5, 2.5, 4, 6, 10, 16, 25, 35*, 50*, 70*, 95*, 120*			
5G	1.5, 2.5, 4, 6, 10, 16, 25			
5, 7, 12, 19, 27, 37	1.5			
5, 7, 12, 19	2.5			

^{*} Sector shaped

Class 5:

No of	Cross sectional area [mm ²]
cores	
1	25, 35, 50, 70, 95, 120, 150, 185, 240, 300
2	1.5, 2.5, 4, 6
3	35, 50, 70, 95, 120, 150, 185
4	35, 50, 70, 95, 120, 150, 185
5G	35, 50, 70, 95

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2020-01	General construction and test methods of	
		power, control and instrumentation cables	
		for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360:	
		Insulating and sheathing materials for	
		shipboard and offshore units, power,	
		control, instrumentation and	
		telecommunication cables.	
IEC 60092-353	2011-08	Electrical installations in ships - Part 353:	
		Power cables for rated voltages 1 kV and 3	
		kV	
IEC 60332-3-22	2018-07	Tests on electric cables under fire	Charred portion of
		conditions - Part 3-22: Test for vertical	sample does not
		flame spread of vertically mounted	exceed 2,5m above

Form code: TA 1411a Revision: 2015-05 www.dnvgl.com Page 2 of 3

Job Id: **262.1-011072-3** Certificate No: **TAE00000SV**

Revision No: 1

		bunched wires or cables - Category A	bottom edge of
			burner.
IEC 60754-1:2011	2019-11	Test on gases evolved during combustion	Low Halogen:
+AMD1:2019 CSV		of materials from cables - Part 1:	
		Determination of the halogen acid gas	
		content	
IEC 60754-2:2011	2019-11	Test on gases evolved during combustion	Halogen free:
+AMD1:2019 CSV		of materials from cables - Part 2:	
		Determination of acidity (by pH	
		measurement) and conductivity	
IEC 61034-	2013-07	Measurement of smoke density of cables	Low smoke
1&2:2005	2013-09	burning under defined conditions –	Light
+AMD1:2013		Test apparatus, procedure and	transmittance >60%
+AMD2:2019 CSV		requirements	

Marking of product

PRYSMIAN (FI20) - LM-HF or TEMAR PHFX-U - size - 0,6/1kV - 60092-353 - 60332-3-22 - Year

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE

Form code: TA 1411a Revision: 2015-05 www.dnvgl.com Page 3 of 3