

Eaton 283032

Catalog Number: 283032

Eaton xComfort BF LV systems Final Distribution Boards.
Complete surface-mounted flat distribution board, white, 24 SU per row, 4 rows, type C



General specifications

Product Name	Catalog Number
Eaton xComfort BF small distribution board	283032
	Model Code
	BF-O-4/96-C
EAN	Product Length/Depth
4015082830328	775 mm
Product Height	Product Width
150 mm	565 mm
Product Weight	Compliances
12.4 kg	RoHS conform
Certifications	
IEC/EN 61439-1	
IEC/EN 61439-3	
IEC/EN 62208	

Product specifications

10.11 Short-circuit rating

Is the panel builder's responsibility.

RAL-number

9016

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

Mounting method

Surface mounted (plaster)

Surface mounting

DIN-rail

10.2.5 Lifting

Does not apply to enclosures without lifting aids.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Fitted with:

Enclosure

Door with three-point turn-lock

Front plates

DIN rail mounting frame

Neutral-/protective conductor terminal

Cable gland plate inserts (top)

10.8 Connections for external conductors

Is the panel builder's responsibility.

Cover/door model

Closed

Module rack type

Rail frame

Special features

IP30 Protection Class I Steel sheet enclosure white (RAL 9016)

Cable entry postion

Cable entries on top and bottom

Built-in width

565 mm

Color

White

Resources

Brochures

[eaton-xcomfort-compact-distribution-boxes-brochure-br014015en-en-us.pdf](#)

Catalogues

[eaton-xcomfort-compact-distribution-catalog-ca015004en-en-us.pdf](#)

Certification reports

[DA-DC-03_xComfort_BF](#)

Drawings

[eaton-xcomfort-bf-lv-systems-dimensions.eps](#)

Installation instructions

[eaton-xcomfort-bf-o-instruction-leaflet-il170757001-z.pdf](#)

Traffic white (RAL 9016)

Built-in depth

775 mm

Features

EMC-version

Earthing terminal block

Neutral terminal block

10.9.3 Impulse withstand voltage

Does not apply to basic enclosures as defined in EN 62208.

10.6 Incorporation of switching devices and components

Is the panel builder's responsibility.

Built-in height

150 mm

10.5 Protection against electric shock

$< 0.1 \Omega$; meets the product standard's requirements.

Cover/door color

White

Used with

BF flat distribution board

Basic device

Installation distribution board

Number of module space units per row

24

Cover/door type

Door

Single

10.13 Mechanical function

Meets the product standard's requirements.

10.2.6 Mechanical impact

IK07

10.9.4 Testing of enclosures made of insulating material

Does not apply to metal enclosures.

10.3 Degree of protection of assemblies

IP30

Application

Indoor (installation site)

Internal depth

131 mm

Closure type

Other

Protective shrouding material

Metal

Voltage rating at AC

415 V AC

Frequency rating of contacts

50 Hz / 60 Hz

Number of rows

4

Protection class

I (earthed)

Width in number of modular spacings

24

Heat diss. ambient 35°C delta T:35°C wall mount starting encl. top (IEC 60890)

98 W

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.9.2 Power-frequency electric strength

U_i = 415 V AC

Degree of protection

IP30

IK07 (impact resistance)

Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890)

51 W

Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890)

47 W

Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890)

103 W

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Heat diss. ambient 35°C delta T: 35°C wall mount middle encl.

[top \(IEC 60890\)](#)

94 W

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Functions

Basic device

Material

Sheet steel, powder-coated

Ambient operating temperature details

-5 °C - 40 °C

Heat diss. ambient 35°C delta T:20°C wall mount starting encl.
[top \(IEC 60890\)](#)

49 W

Enclosure material

Steel

Type

Basic device BF flat DBO Installation distribution boards

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Not relevant to indoor installations.

10.2.7 Inscriptions

Meets the product standard's requirements.

Terminal type

Screw terminals

PE and N terminal number and cross section

PE: 2 x 25 mm² + 43 x 16 mm²

N: 2 x 25 mm² + 43 x 16 mm²



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)