

Complete flush-mounted flat distribution board, white, 24 SU per row, 3 rows, type C



Part no. **BF-U-3/72-C**
283048

General specifications		
Product name		Eaton xComfort BF small distribution board
Part no.		BF-U-3/72-C
EAN		4015082830489
Product Length/Depth		640 millimetre
Product height		150 millimetre
Product width		620 millimetre
Product weight		10.8 kilogram
Compliances		RoHS conform
Certifications		IEC/EN 61439-1 IEC/EN 61439-3 IEC/EN 62208
Product Tradename		xComfort BF
Product Type		Small distribution board
Product Sub Type		None
Delivery program		
Type		Basic device BF flat DBO Installation distribution boards
Application		Indoor (installation site)
Color		White Traffic white (RAL 9016)
Technical Data - Electrical		
Voltage rating at AC		415 V AC
Frequency rating of contacts		50 Hz / 60 Hz
Technical Data - Mechanical		
Closure type		Other
Width in number of modular spacings		24
Mounting method		Flush mounted (plaster) Hollow wall Flush mounting Hollow-wall mounting and flush mounting DIN-rail
Material		Sheet steel, powder-coated
Degree of protection		IP30 IK07 (impact resistance)
Number of module space units per row		24
Number of rows		3
Terminal type		Screw terminals
PE and N terminal number and cross section		N: 2 x 25 mm ² + 43 x 16 mm ² PE: 2 x 25 mm ² + 43 x 16 mm ²
Built-in depth		127 mm
Built-in height		570 mm
Built-in width		560 mm
Internal depth		127 mm
Cover/door color		White
Cover/door model		Closed
Cover/door type		Door Single
Module rack type		Rail frame
Protective shrouding material		Metal
Temperature-rise verification as per IEC 60890		
Heat diss. ambient 35°C delta T:20°C flush mount individ. encl. top(IEC 60890)		41 W

Heat diss. ambient 35°C delta T:35°C flush mount individ. encl. top(IEC 60890)			82 W
Design verification as per IEC/EN 61439 - technical data			
Ambient operating temperature details			-5 °C - 40 °C
Design verification as per IEC/EN 61439			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact			IK07
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			IP30
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Ui = 415 V AC
10.9.3 Impulse withstand voltage			Does not apply to basic enclosures as defined in EN 62208.
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			Meets the product standard's requirements.
Additional information			
Features			EMC-version Earthing terminal block Neutral terminal block
Fitted with:			Front plates DIN rail mounting frame Wall trough with door frame Neutral-/protective conductor terminal Door with three-point turn-lock
Functions			Basic device
Protection class			I (earthed)
RAL-number			9016
Special features			IP30 Protection Class I Steel sheet enclosure white (RAL 9016)
Used with			Installation distribution board BF flat distribution board Basic device

Technical data ETIM 8.0

Distribution boards (EG000023) / Small distribution board (EC000214)			
Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Small distribution board (ecI@ss10.0.1-27-14-24-09 [ACN387011])			
Mounting method			Flush mounted (plaster)
Number of rows			3
Width in number of modular spacings			24
Type of cover			Door
Cover model			Closed
Transparent cover/door			No
Material housing			Steel
Height		mm	150
Width		mm	620
Depth		mm	640
Built-in depth		mm	127
Built-in height		mm	570

Built-in width		mm	560
Internal depth		mm	127
Earthing terminal block			Yes
Neutral terminal block			Yes
DIN-rail			Yes
With mounting plate			No
Extension possible			No
EMC-version			Yes
Colour			White
RAL-number			9016
Degree of protection (IP)			IP30
With lock			No
Type of closure			Other
Signal passing door			No