

Eaton 072737

Catalog Number: 072737

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker, 1.5 kW, 2.5 - 4 A, Screw terminals



General specifications

Product Name

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker

Catalog Number

072737

Model Code

PKZM0-4

EAN

4015080727378

Product Length/Depth

76 mm

Product Height

93 mm

Product Width

45 mm

Product Weight

0.284 kg

Certifications

CSA

UL 60947-4-1

CE

CSA Class No.: 3211-05

IEC/EN 60947-4-1

IEC/EN 60947

UL Category Control No.: NLRV

CSA File No.: 165628

UL File No.: E36332

VDE 0660

UL

CSA-C22.2 No. 60947-4-1-14

Features & Functions

Actuator type

Turn button

Features

Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)

Functions

Phase failure sensitive

Motor protection

Number of poles

Three-pole

General

Explosion safety category for dust

ATEX dust-ex-protection, PTB 10, ATEX 3013, Ex II(2) GD

Lifespan, electrical

100,000 operations

Lifespan, mechanical

100,000 Operations

Mounting position

Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.

Operating frequency

40 Operations/h

Overvoltage category

III

Pollution degree

3

Product category

Motor protective circuit breaker

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp)

6000 V AC

Shock resistance

25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Suitable for

Branch circuit: Manual type E if used with terminal, or suitable for group installations, (UL/CSA)

Also motors with efficiency class IE3

Temperature compensation

-5 - 40 °C to IEC/EN 60947, VDE 0660

-25 - 55 °C, Operating range

≤ 0.25 %/K, residual error for T > 40°

Climatic environmental conditions

Altitude

Terminal capacities

Terminal capacity (flexible with ferrule)

Max. 2000 m

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

55 °C

Ambient operating temperature (enclosed) - min

25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient storage temperature - min

40 °C

Ambient storage temperature - max

80 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

2 x (1 - 6) mm², ferrule to DIN 46228

1 x (1 - 6) mm², ferrule to DIN 46228

Terminal capacity (solid)

1 x (1 - 6) mm²

2 x (1 - 6) mm²

Terminal capacity (solid/stranded AWG)

18 - 10

Stripping length (main cable)

10 mm

Tightening torque

1.7 Nm, Screw terminals, Main cable

1 Nm, Screw terminals, Control circuit cables

Electrical rating

Rated frequency - min

50 Hz

Rated frequency - max

60 Hz

Rated operational current (I_e)

4 A

Rated operational power at AC-3, 220/230 V, 50 Hz

0.75 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

1.5 kW

Rated operational voltage (U_e) - min

690 V

Rated operational voltage (U_e) - max

690 V

Rated uninterrupted current (I_u)

4 A

Short-circuit rating

Short-circuit current

60 kA DC, up to 250 V DC, Main conducting paths

Short-circuit current rating (group protection)

600 A, 600 V High Fault, max. CB, SCCR (UL/CSA)

50 kA, 600 V High Fault, CB, SCCR (UL/CSA)

Motor rating

Assigned motor power at 115/120 V, 60 Hz, 1-phase

0.125 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase

0.75 HP

50 kA, 600 V High Fault, Fuse, SCCR (UL/CSA)
600 A, 600 V High Fault, max. Fuse, SCCR (UL/CSA)

Short-circuit current rating (type E)

65 kA, 480 Y/277 V, SCCR (UL/CSA)
65 kA, 240 V, SCCR (UL/CSA)
Accessories required BK25/3-PKZ0-E
50 kA, 600 Y/347 V, SCCR (UL/CSA)

Short-circuit release

± 20% tolerance, Trip blocks
Basic device fixed 15.5 x Iu, Trip Blocks
62 A, Irm, Setting range max.

Assigned motor power at 230/240 V, 60 Hz, 1-phase
0.33 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase
0.75 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase
2 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase
3 HP

Communication

Connection
Screw terminals

Trip blocks

Overload release current setting - min
2.5 A

Overload release current setting - max
4 A

Tripping characteristic
Overload trigger: tripping class 10 A

Design verification

Equipment heat dissipation, current-dependent Pvid
5.33 W

Heat dissipation capacity Pdis
0 W

Heat dissipation per pole, current-dependent Pvid
1.78 W

Rated operational current for specified heat dissipation (In)
4 A

Static heat dissipation, non-current-dependent Pvs
0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Resources

Brochures

Save time and space thanks to the new link module PKZM0-XDM32ME

Motor Starters in System xStart - brochure

Catalogues

Product Range Catalog Switching and protecting motors

Switching and protecting motors - catalog

Characteristic curve

[eaton-manual-motor-starters-characteristic-characteristic-curve-011.eps](#)

[eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps](#)

[eaton-manual-motor-starters-characteristic-characteristic-curve-009.eps](#)

Declarations of conformity

[DA-DC-00004921.pdf](#)

[DA-DC-00004892.pdf](#)

Drawings

[eaton-manual-motor-starters-pkz-dimensions.eps](#)

[eaton-manual-motor-starters-pkz-dimensions-002.eps](#)

[eaton-manual-motor-starters-pkzm0-dimensions-003.eps](#)

[eaton-manual-motor-starters-pkzm0-3d-drawing-008.eps](#)

[eaton-manual-motor-starters-pkzm0-3d-drawing-004.eps](#)

[eaton-manual-motor-starters-mounting-3d-drawing-002.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

eCAD model

[DA-CE-ETN.PKZM0-4](#)

Installation instructions

[IL03407011Z](#)

[IL03402034Z](#)

Installation videos

[WIN-WIN with push-in technology](#)

Manuals and user guides

[eaton-motor-protective-circuit-breaker-pkzm0-overload-monitoring-exe-manual-mn03402003z-de-de-en-us.pdf](#)

[IL122023ZU](#)

mCAD model

[DA-CS-pkzm0](#)

[DA-CD-pkzm0](#)

Wiring diagrams

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

[eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps](#)

[eaton-manual-motor-starters-starter-nzm-mccb-wiring-diagram.eps](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)