
## Eaton 248411

## Catalog Number: 248411

Eaton Distribution parts. Motor-Protective Circuit-Breakers, 6,3-10A, 3p



**Product Name** 

Eaton Distribution parts

Model Code

Z-MS-10/3

Product Length/Depth

80 mm

**Product Width** 

54 mm

Compliances

RoHS conform

Catalog Number

248411

EAN

4015082484118

**Product Height** 

75 mm

**Product Weight** 

0.366 kg



## **Product specifications**

Rated operating voltage (Ue) - min

400 V

Rated operational current for specified heat dissipation (In)

10 A

Switch off technique

Magnetic

Overload release current setting - min

6.3 A

Adjustment range undelayed short-circuit release - min

78 A

Heat dissipation per pole, current-dependent

2.33 W

Device construction

Complete device in housing

Rated operating power at AC-3, 230 V

0 kW

Electrical connection type of main circuit

Screw connection

Rated operating power at AC-3, 400  $\rm V$ 

4 kW

Number of poles

Three-pole

Fitted with:

Thermal protection

Rated uninterrupted current (Iu)

10 A

Rated operating voltage (Ue) - max

400 V

Equipment heat dissipation, current-dependent

7 W

Adjustment range undelayed short-circuit release - max

105 A

Rated short-circuit breaking capacity at 400 V AC

10 kA

Adjustment range short-term delayed short-circuit release - min

## Resources

Certification reports

DA-DC-03\_Z-MS

**Drawings** 

eaton-dimensions-mas-ms7.jpg

eaton-wiring-diagram-ms7-3p.jpg

Diagr\_MS\_10A

78 A

Overload release current setting - max

10 A

Actuator type

Rocker lever

Degree of protection

IP20



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia