

Eaton 216382

Catalog Number: 216382

Eaton Moeller® series M22 Contact element, Screw terminals, Base fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-KC01



General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Accessory Contact element	216382
	Model Code
	M22-KC01
EAN	Product Length/Depth
4015082163822	38 mm
Product Height	Product Width
10 mm	32 mm
Product Weight	Compliances
0.01 kg	CE Marked
Certifications	Catalog Notes
IEC 60947-5 CSA Std. C22.2 No. 14-05 EN 60947-5 CSA Std. C22.2 No. 94-91 UL 508 CSA Class No.: 3211-03 CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 CE CSA File No.: 012528 IEC/EN 60947-5 UL UL File No.: E29184 UL Category Control No.: NKCR CSA IEC 60947-5-1	Contacts with safety function, by positive opening to IEC/EN 60947-5-1

Product specifications

Contact configuration

1 NC

Rated operational current for specified heat dissipation (I_n)

6 A

Terminal capacity (flexible with ferrule)

0.5 - 1.5 mm²

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Lamp holder

None

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting method

Floor fastening

Operating torque

0.8 Nm

Amperage Rating

6A

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Force for positive opening - min

15 N

10.8 Connections for external conductors

Is the panel builder's responsibility.

Actuator travel and actuation force (DIN EN 60947-5-1)

4.8 mm

Rated conditional short-circuit current (I_q)

1 kA

Terminal capacity (stranded)

Resources

Brochures

RMQ Titan - brochure

RMQ Titan emergency stop push button - Flyer

RMQ Small E-Stop - Flyer

RMQ Flat Enclosure - Flyer

RMQ MCI - Flyer

Catalogs

Product Range Catalog Command and Indication Control Circuit Devices, Signal Towers

Flip catalog - Product Range Catalog - Command and indication

Certification reports

DA-DC-00004176.pdf

DA-DC-00004141.pdf

DA-DC-00004180.pdf

DA-DC-00004135.pdf

DA-DC-00004134.pdf

000Z425

DA-DC-00004157.pdf

Drawings

eaton-operating-pushbutton-m22-dimensions-003.eps

eaton-operating-contact-m22-contact-element-3d-drawing-003.eps

eaton-general-standards-000Z425.jpg

eaton-operating-devices-adapter-flow-diagram-004.eps

eaton-operating-adapter-m22-contact-element-flow-diagram-004.eps

eCAD model

ETN.M22-KC01

Installation instructions

IL04716002Z

eaton-operating-devices-rmq-titan-m22-instruction-leaflet-ii047018zu.pdf

Installation videos

RMQ Flat Design

mCAD model

DA-CS-kontaktelement_schraube_boden

DA-CD-kontaktelement_schraube_boden

System overview

0.5 - 2.5 mm²

[Pilot devices - selection aid](#)

[Ambient operating temperature - max](#)

[Wiring diagrams](#)

70 °C

[eaton-operating-contact-m22-contact-element-wiring-diagram-003.eps](#)

[Climatic proofing](#)

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

[Knob travel](#)

5.7 mm

[Connection to SmartWire-DT](#)

No

[Lifespan, electrical](#)

700,000 Operations (at 230 V, AC-15, 3 A)

1,600,000 Operations (at 230 V, 0.5 A)

1,000,000 Operations (at 230 V, AC-15, 1 A)

1,200,000 Operations (at 12 V, DC-13, 2.8 A)

[Static heat dissipation, non-current-dependent Pvs](#)

0 W

[Rated operational current \(I_e\) at AC-15, 500 V](#)

2 A

[10.9.3 Impulse withstand voltage](#)

Is the panel builder's responsibility.

[Ambient operating temperature - min](#)

-25 °C

[10.6 Incorporation of switching devices and components](#)

Does not apply, since the entire switchgear needs to be evaluated.

[10.5 Protection against electric shock](#)

Does not apply, since the entire switchgear needs to be evaluated.

[Rated operational current \(I_e\) at AC-15, 220 V, 230 V, 240 V](#)

6 A

[Electric connection type](#)

Screw connection

[10.13 Mechanical function](#)

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

[Rated operational current \(I_e\) at DC-13, 42 V](#)

1.7 A

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Number of contacts (normally closed contacts)

1

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent P_{vid}

0.11 W

Rated operational current (I_e) at AC-15, 380 V, 400 V, 415 V

4 A

Operating frequency

3600 Operations/h

Short-circuit protection

PKZM0-10/FAZ-B6/1, Contacts, Max. short-circuit protective device, Fuseless

Number of switches (fault signal)

0

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Rated operational current (I_e) at DC-13, 60 V

1.2 A

Rated operational current (I_e) at AC-15, 115 V

6 A

Terminal capacity (solid)

0.75 - 2.5 mm²

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Connection type

Base fixing

Single contact

Lifespan, mechanical

5,000,000 Operations

Rated operational current (I_e) at DC-13, 220 V, 230 V

0.3 A

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Control circuit reliability

1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)

1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)

Overvoltage category

III

Degree of protection

IP20

Pollution degree

3

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Actuating force - max

5 N

Rated impulse withstand voltage (U_{imp})

6000 V AC

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Number of contacts (normally open contacts)

0

Short-circuit protection rating

Max. 10 A gG/gL, Fuse, Contacts

Model

Top mounting

Rated operational current (I_e) at DC-13, 110 V

0.6 A

Number of contacts (change-over contacts)

0

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal
shock 11 ms

Rated insulation voltage (U_i)

500 V

Rated operational current (I_e) at DC-13, 24 V

3 A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)