

Eaton 216590

Catalog Number: 216590

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Flat, momentary, black, Blank, Bezel: titanium

General specifications



Product Name	Catalog Number
Eaton Moeller® series M22 Pushbutton	216590
Model Code	EAN
M22-D-S	4015082165901
Product Length/Depth	Product Height
30 mm	30 mm
Product Width	Product Weight
30 mm	0.009 kg
Compliances	Certifications
CE Marked	IEC 60947-5
	EN 60947-5
	UL 508
	CSA Std. C22.2 No. 94-91
	CSA Std. C22.2 No. 14-05
	VDE
	CSA
	CSA-C22.2 No. 94-91
	UL File No.: E29184
	CE
	IEC/EN 60947
	UL Category Control No.: NKCR
	VDE 0660
	UL
	CSA Class No.: 3211-03
	CSA File No.: 012528
	CSA-C22.2 No. 14-05
	IEC/EN 60947-5
	DNV
	CL

Funcities & kenmerken

Bezel color

Chrome

Bezel material

Plastic

Color

Black

Design

Flat

Classical

Fitted with:

Front ring

Inscription

Blank

Algemeen

Degree of protection

IP69K

NEMA 13

NEMA 3R

IP67

IP66

NEMA 4X

NEMA 12

Degree of protection (front side)

NEMA 4X

IP67/IP69K

Lifespan, mechanical

5,000,000 Operations

Opening diameter

22.5 mm

Operating frequency

3600 Operations/h

Product category

RMQ-Titan

Size

Front dimensions: 22 x 22 mm

Type

Pushbutton actuator

Omgevingsomstandigheden, mechanisch

Mounting position

As required

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Klimatologische milieu-omstandigheden

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Ambient storage temperature - min

40 °C

Ambient storage temperature - max

80 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Communicatie

Connection to SmartWire-DT

Yes

With SWD-RMQ connections

Actuator

Actuating force

5 N

Actuator color

Black

Actuator function

Spring-return

Momentary

Contacten

Force for positive opening - min

0 N

Ontwerpverificatie

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Rated operational current for specified heat dissipation (I_n)

0 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Brochures

[RMQ Titan - brochure](#)

[RMQ MCI - Flyer](#)

[RMQ Flat Enclosure - Flyer](#)

[RMQ Small E-Stop - Flyer](#)

[RMQ Titan emergency stop push button - Flyer](#)

Catalogs

[Product Range Catalog Command and Indication Control Circuit Devices, Signal Towers](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

Certification reports

[DA-DC-00004157.pdf](#)

[DA-DC-00004135.pdf](#)

Drawings

[eaton-operating-pushbutton-m22-dimensions-004.eps](#)

[eaton-operating-pushbutton-m22-dimensions-003.eps](#)

[eaton-operating-actuation-m22-dimensions-002.eps](#)

[eaton-operating-button-symbol-005.eps](#)

[eaton-operating-samrtwire-m22-3d-drawing.eps](#)

[eaton-general-m22-symbol.eps](#)

[eaton-general-m22-standards.eps](#)

[eaton-general-approval-m22-symbol.eps](#)

eCAD model

[ETN.M22-D-S](#)

Installation instructions

[eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf](#)

[IL04716002Z](#)

Installation videos

[RMQ Flat Design](#)

mCAD model

[DA-CS-drucktaste_flach](#)

[DA-CD-drucktaste_flach](#)

System overview

[Pilot devices - selection aid](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)