

## OTL16 red 1xAl/Cu 1,5-16mm<sup>2</sup> 1000V Universal terminal

<b>SKU</b>	MAA1016R10
<b>EAN</b>	4744397013767
<b>Color</b>	Red
<b>Wire material</b>	Al/Cu
<b>Cross-section min. (mm<sup>2</sup>)</b>	1,5
<b>Cross-section max. (mm<sup>2</sup>)</b>	16
<b>Input wire min. (mm<sup>2</sup>)</b>	1,5
<b>Input wire max. (mm<sup>2</sup>)</b>	16
<b>Output wire min. (mm<sup>2</sup>)</b>	1,5
<b>Output wire max. (mm<sup>2</sup>)</b>	16
<b>Number of connections</b>	2
<b>Nominal current (A)</b>	82 (Cu) / 75 (Al)
<b>Nominal voltage (V)</b>	1000
<b>Service temperature (°C)</b>	80
<b>Material</b>	Tin-plated aluminium, polyamide PA66
<b>Mounting method</b>	DIN rail
<b>Item width (mm)</b>	13,5
<b>Item length (mm)</b>	45



<b>Item height (mm)</b>	39,5
<b>Item weight (g)</b>	15
<b>Screw</b>	Hex 4
<b>Tightening torque (Nm)</b>	1,5 Nm (1,5 - 6 mm <sup>2</sup> )7 Nm (10 - 16 mm <sup>2</sup> )
<b>IP rating</b>	IP20
<b>Certification</b>	EN 61238-1; EN60947-7-1
<b>Flame resistance</b>	UL94 V0
<b>CN8 code</b>	85369010
<b>Package quantity (pcs)</b>	30