

## OTL240-2 ye/gr 2xAl/Cu 35-240mm<sup>2</sup> 1000V Universal terminal

<b>SKU</b>	MAA2240Y10
<b>EAN</b>	4744397014245
<b>Color</b>	Yellow/green
<b>Wire material</b>	Al/Cu
<b>Cross-section min. (mm<sup>2</sup>)</b>	35
<b>Cross-section max. (mm<sup>2</sup>)</b>	240
<b>Input wire min. (mm<sup>2</sup>)</b>	35
<b>Input wire max. (mm<sup>2</sup>)</b>	240
<b>Output wire min. (mm<sup>2</sup>)</b>	35
<b>Output wire max. (mm<sup>2</sup>)</b>	240
<b>Number of connections</b>	4
<b>Nominal current (A)</b>	425 (Cu) / 380 (Al)
<b>Nominal voltage (V)</b>	1000
<b>Service temperature (°C)</b>	80
<b>Material</b>	Tin-plated aluminium, polyamide PA66
<b>Mounting method</b>	DIN rail, screw
<b>Item width (mm)</b>	60
<b>Item length (mm)</b>	106



<b>Item height (mm)</b>	65
<b>Item weight (g)</b>	340
<b>Screw</b>	Hex 8
<b>Tightening torque (Nm)</b>	26 Nm (35 - 120 mm <sup>2</sup> )40 Nm (150 - 240 mm <sup>2</sup> )
<b>IP rating</b>	IP20
<b>Certification</b>	EN 61238-1; EN60947-7-1
<b>Flame resistance</b>	UL94 V0
<b>CN8 code</b>	85369010
<b>Package quantity (pcs)</b>	3