

## OTL95-3 blue 3xAl/Cu 6-95mm<sup>2</sup> 1000V Universal terminal

|  |                                      |
|--|--------------------------------------|
| <b>SKU</b>                                 | MAA3095B10                           |
| <b>EAN</b>                                 | 4744397014320                        |
| <b>Color</b>                               | Blue                                 |
| <b>Wire material</b>                       | Al/Cu                                |
| <b>Cross-section min. (mm<sup>2</sup>)</b> | 6                                    |
| <b>Cross-section max. (mm<sup>2</sup>)</b> | 95                                   |
| <b>Input wire min. (mm<sup>2</sup>)</b>    | 6                                    |
| <b>Input wire max. (mm<sup>2</sup>)</b>    | 95                                   |
| <b>Output wire min. (mm<sup>2</sup>)</b>   | 6                                    |
| <b>Output wire max. (mm<sup>2</sup>)</b>   | 95                                   |
| <b>Number of connections</b>               | 6                                    |
| <b>Nominal current (A)</b>                 | 245 (Cu) / 220 (Al)                  |
| <b>Nominal voltage (V)</b>                 | 1000                                 |
| <b>Service temperature (°C)</b>            | 80                                   |
| <b>Material</b>                            | Tin-plated aluminium, polyamide PA66 |
| <b>Mounting method</b>                     | DIN rail, screw                      |
| <b>Item width (mm)</b>                     | 59                                   |
| <b>Item length (mm)</b>                    | 84                                   |



|                               |   |
|-------------------------------|---|
| <b>Item height (mm)</b>       | 51  |
| <b>Item weight (g)</b>        | 178   |
| <b>Screw</b>                  | Hex 6   |
| <b>Tightening torque (Nm)</b> | 12 Nm (6 - 25 mm <sup>2</sup> )22 Nm (35 - 95 mm <sup>2</sup> ) |
| <b>IP rating</b>              | IP20  |
| <b>Certification</b>          | EN 61238-1; EN60947-7-1   |
| <b>Flame resistance</b>       | UL94 V0   |
| <b>CN8 code</b>               | 85369010  |
| <b>Package quantity (pcs)</b> | 6   |