

## OJL200A blue in 1xAl/Cu70 out 6xCu 16mm<sup>2</sup> Distribution block

<b>SKU</b>	MAB1201B10
<b>EAN</b>	4744397018861
<b>Color</b>	Blue
<b>Wire material</b>	Al/Cu
<b>Cross-section min. (mm<sup>2</sup>)</b>	2,5
<b>Cross-section max. (mm<sup>2</sup>)</b>	70
<b>Input wire min. (mm<sup>2</sup>)</b>	1 x 10
<b>Input wire max. (mm<sup>2</sup>)</b>	1 x 70
<b>Output wire min. (mm<sup>2</sup>)</b>	6 x 2,5
<b>Output wire max. (mm<sup>2</sup>)</b>	6 x 16
<b>Number of connections</b>	7
<b>Nominal current (A)</b>	200 (Cu) / 160 (Al)
<b>Nominal voltage (V)</b>	1000
<b>Service temperature (°C)</b>	80
<b>Material</b>	Tin-plated aluminium, polyamide PA66
<b>Mounting method</b>	DIN rail, screw
<b>Item width (mm)</b>	32,4
<b>Item length (mm)</b>	75,8



<b>Item height (mm)</b>	46
<b>Item weight (g)</b>	84
<b>Screw</b>	Hex 3 / 5
<b>Tightening torque (Nm)</b>	3 Nm (2,5 - 16 mm <sup>2</sup> ) 6 Nm (25 - 35 mm <sup>2</sup> ) 10 Nm (50 - 70 mm <sup>2</sup> )
<b>IP rating</b>	IP20
<b>Certification</b>	EN 61238-1:2003; EN 60947-7-1:2009
<b>CN8 code</b>	85369010
<b>Package quantity (pcs)</b>	24