

Busbar, isolated, 63A, 1p, 1Mod

Part no. **Z-GV-10/1P-1TE**
270339

General specifications		
Product name		Eaton Distribution parts
Part no.		Z-GV-10/1P-1TE
EAN		4015082703394
Product Length/Depth		16.8 millimetre
Product height		14.4 millimetre
Product width		1016 millimetre
Product weight		0.22 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Color		Other
Cross section		10 mm ²
Electric connection type		Fork
Features		Insulated Can be cut to size
Number of modular spacings		1
Number of phases		1
Number of poles		Single-pole
Pitch dimensions		17.8 mm
Rated conditional short-circuit current (I _q)		25 kA
Rated operational voltage (U _e) - max		415 V
Rated short-time withstand current (I _{cw})		0 kA
Rated surge voltage		0 kV
Rated uninterrupted current (I _u)		63 A
Suitable for		57 devices
Suitable for number of devices		57

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss10.0.1-27-37-13-06 [ACN992011])		
Number of phases		1
Number of poles		1
Suitable for number of devices		57
Module width	mm	17.8
Cross section	mm ²	10
Length	mm	16.8
Width in number of modular spacings		1
Rated permanent current I _u	A	63
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	0
Conditioned rated short-circuit current I _q	kA	25

Max. rated operation voltage U _e	V	415
Rated short-time withstand current I _{cw}	kA	0
Suitable for devices with N-conductor		No
Suitable for devices with auxiliary switch		No
Colour		Other