## EV busbars 3Ph., 12HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM



**EVG-3PHAS/12MODUL** Part no.

215639

**EL Number** 1657143

(Norway)

| (Norway)                                     |  |
|--|--|
| General specifications                       |  |
| Product name                                 | Eaton Moeller series busbar  |
| Part no.                                     | EVG-3PHAS/12MODUL  |
| EAN  | 4015082156398  |
| Product Length/Depth                         | 210 millimetre   |
| Product height                               | 30 millimetre  |
| Product width                                | 10 millimetre  |
| Product weight                               | 0.089 kilogram   |
| Compliances                                  | RoHS conform   |
| Product Tradename                            | None   |
| Product Type                                 | Busbar   |
| Product Sub Type                             | None   |
| Product Specification Details                |  |
| Accessory/spare part type                    | Busbar for residual current circuit breakers<br>Busbar for miniature circuit breaker<br>Busbar for combined residual current/power circuit breaker |
| Color  | Other  |
| Cross section                                | 10 mm <sup>2</sup>   |
| EL number                                    | 1657143  |
| Electric connection type                     | Fork   |
| Features                                     | Insulated  |
| Functions                                    | Busbar   |
| Number of modular spacings                   | 12   |
| Number of phases                             | 3  |
| Number of poles                              | Three-pole   |
| Pitch dimensions                             | 0 mm   |
| Rated conditional short-circuit current (Iq) | 25 kA  |
| Rated operational voltage (Ue) - max         | 500 V  |
| Rated short-time withstand current (Icw)     | 0 kA   |
| Rated surge voltage                          | 4 kV   |
| Rated uninterrupted current (Iu)             | 63 A   |
| Suitable for                                 | 4 devices  |
| Suitable for number of devices               | 4  |
| Туре   | Busbar<br>EVG  |
| Used with                                    | EVG<br>Busbar  |
|  |  |

## **Technical data ETIM 8.0**

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

| [ACN992011])                        |     |     |  |
|-------------------------------------|-----|-----|--|
| Number of phases                    |     | 3   |  |
| Number of poles                     |     | 3   |  |
| Suitable for number of devices      |     | 4   |  |
| Module width                        | mm  | 0   |  |
| Cross section                       | mm² | 10  |  |
| Length                              | mm  | 210 |  |
| Width in number of modular spacings |     | 12  |  |
| Rated permanent current lu          | А   | 63  |  |

| Type of electric connection                |    | Fork  |
|--|----|-------|
| Insulated                                  |    | Yes   |
| Rated surge voltage                        | kV | 4     |
| Conditioned rated short-circuit current Iq | kA | 25    |
| Max. rated operation voltage Ue            | V  | 500   |
| Rated short-time withstand current lcw     | kA | 0     |
| Suitable for devices with N-conductor      |    | No    |
| Suitable for devices with auxiliary switch |    | No    |
| Colour                                     |    | Other |