

PRODUCT-DETAILS

## MLBL-07R MLBL-07R LED block



General Information	
Extended Product Type	MLBL-07R
Product ID	1SFA611621R1071
EAN	7320500544860
Catalog Description	MLBL-07R LED block
Long Description	The MLBL-07R LED block is: - Red - Illuminated - Front mounting - 230 V This LED block is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free

## Ordering10 pieceMinimum Order Quantity10 pieceCustoms Tariff Number85369001

## **Popular Downloads**

Data Sheet, Technical Information 1SFC151007C02\_\_

MLBL-07R 2

Instructions and 1SFC151011M0201 Manuals

Dimensions	
Product Net Width	0.01 m
Product Net Height	0.044 m
Product Net Depth / Length	0.042 m
Product Net Weight	0.01 kg

Technical	
Ambient Air	Operation -25 +70 °C
Temperature	Storage -40 +85 °C
Color	Rec
Illumination	Illuminated
Lamp Type	230 V AC, integrated LED
Mounting Type	Front mounting
Degree of Protection	Terminals IP20
Rated Frequency (f)	50 / 60 H:
Rated Operational Voltage	230 V AC
Connecting Capacity	Flexible with Ferrule 1 x 0.752.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.752.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.752.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.752.5 mm <sup>2</sup> Flexible 1 x 0.75 2.5 mm <sup>2</sup> Flexible 2 x 0.75 2.5 mm <sup>2</sup> Solid 1 x 0.752.5 mm <sup>2</sup> Solid 2 x 0.752.5 mm <sup>2</sup>
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.9 N·m
Wire Stripping Length	8 mm
Suitable For	MCBH-00 MCBH5-00 MCBH5-00 MPH MPA MPA MPA MPMT MPMT MPMPS M2SSI M2SSS M2SSS M2SSS M2SSS M2SSS M2SSS M3SSS M3SSS M3SSS M3SSS M3SSS M3SSS M3SSS
Suitable for Product Class	MPM Pilot Devices

Technical UL/CSA	
Connecting Capacity	1x 1814 AWG
UL/CSA	2x 1814 AWG

Environmental	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
RoHS Information	2CMT2015-005452
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	SEMKO_SE-56219
CQC Certificate	CQC2008010305274953
cULus Certificate	9AKK107046A9925
Declaration of Conformity - CCC	2020980305001106
Declaration of Conformity - CE	2CMT2015-005452
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	E-14107
EAC Certificate	1SFC150017D1101

Container Information	
Package Level 1 Units	bag 10 piece
Package Level 1 Width	0.135 m
Package Level 1 Depth / Length	0.155 m
Package Level 1 Height	0.025 m
Package Level 1 Gross Weight	0.11 kg
Package Level 1 EAN	7320500372852

Classifications	
Object Classification Code	E
ETIM 6	EC000204 - Lamp holder block for control circuit devices
ETIM 7	EC000204 - Lamp holder block for control circuit devices
ETIM 8	EC000204 - Lamp holder block for control circuit devices
eClass	V11.0 : 27371209
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	2315775
E-Number (Norway)	4373113
E-Number (Sweden)	3705067

MLBL-07R 4

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Pilot\ Devices \rightarrow Accessories$   $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products \rightarrow Pilot\ Devices \rightarrow Modular\ Plastic\ Range$ 







