

PRODUCT DATASHEETSMART+ WIFI FLOOD 20W

SMART+ MULTICOLOR | Floodlights with WiFi technology



AREAS OF APPLICATION

- Building facades

PRODUCT BENEFITS

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options
- Combines the functionality of general lighting and mood lighting

PRODUCT FEATURES

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Mounting bracket for up to 180° tilting
- Type of protection: IP65
- Connection via 0.5 m cable, wiring required



TECHNICAL DATA

Electrical data

| Nominal wattage | 20.00 W |
|-----------------|---------------|
| Nominal voltage | 220240 V |
| Mains frequency | 50/60 Hz |
| Operating mode | Mains voltage |


Photometrical data

| Color temperature | 3000 K |
|---------------------------|---------|
| Color rendering index Ra | ≥80 |
| Light color (designation) | RGBW |
| Luminous efficacy | 63 lm/W |
| Luminous flux | 1260 lm |

Light technical data

| angle | 100.00 ° |
|-------|----------|
|-------|----------|

Dimensions & weight



| Product weight | 380.00 g |
|----------------|----------|
| Length | 152.0 mm |
| Width | 125.0 mm |
| Height | 28.0 mm |

Colors & materials

| Product color | Dark gray |
|----------------|-----------|
| Body material | Aluminum |
| Cover material | Glass |
| Housing color | Dark gray |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
|---------------------------|-----------|

Lifespan

| Number of switching cycles | 30000 |
|----------------------------|-------|
| | |

Additional product data

| Product remark | Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. | |
|-------------------|--|--|
| Mounting location | Wall | |
| Mounting type | Surface | |

Capabilities

| Dimmable | Yes | |
|----------------------------------|---------------------------------|--|
| Type of connection | Cable, 3-pole | |
| Compatible smart home technology | Google Assistant / Amazon Alexa | |

Certificates & standards

| Standards | CE/EAC/REACH/RoHS | |
|--------------------|-------------------|--|
| Protection class | 1 | |
| Type of protection | IP65 | |

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075474628 | Folding carton box 1 | 154 mm x 40 mm x 166 mm | 445.00 g | 1.02 dm ³ |
| 4058075474635 | Shipping carton box 12 | 327 mm x 257 mm x 190 mm | 5748.00 g | 15.97 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.