

Eaton 063961

Catalog Number: 063961

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 2, 90 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

General specifications

Product Name

Eaton Moeller® series B3 Accessory
Three-phase busbar link

Catalog Number

063961

Model Code

B3.0/2-PKZ0

EAN

4015080639619

Product Length/Depth

90 mm

Product Height

34 mm

Product Width

11 mm

Product Weight

0.035 kg

Certifications

CSA-C22.2 No. 14
UL File No.: E36332
CSA File No.: 98494
UL Category Control No.: NLRV
CE
IEC/EN 60947-4-1
CSA
UL 508
CSA Class No.: 3211-06
UL



Catalog Notes

For parallel power feed to several motor-protective circuit-breakers on terminals 1, 3, 5

Features & Functions

Color

Black

Electric connection type

Fork

Features

Insulated

Functions

Can be extended by rotating installation

Number of phases

3

Number of poles

Three-pole

General

Mounting width

45 mm

Overvoltage category

III

Pollution degree

3

Product category

Accessories

Rated impulse withstand voltage (Uimp)

6000 V AC

Suitable for

2 Circuit-breakers

Used with

PKZ0

PKE12

PKE32

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

55 °C

Electrical rating

Rated operational voltage (Ue) - max

690 V

Rated operational voltage (Ue) at AC - max

690 V

Rated uninterrupted current (Iu)

63 A

Short-circuit rating

Rated conditional short-circuit current (Iq)

0 kA

Rated short-time withstand current (Icw)

0 kA

Design verification

Equipment heat dissipation, current-dependent Pvid

3 W

Heat dissipation capacity Pdis

0 W

Heat dissipation per pole, current-dependent Pvid

1 W

Rated operational current for specified heat dissipation (In)

63 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Resources

Brochures

[Save time and space thanks to the new link module PKZM0-XDM32ME](#)

[Motor Starters in System xStart - brochure](#)

Catalogues

[Switching and protecting motors - catalog](#)

[Product Range Catalog Switching and protecting motors](#)

Certification reports

[DA-DC-00004109.pdf](#)

[DA-DC-00004245.pdf](#)

[DA-DC-00004544.pdf](#)

[DA-DC-00004601.pdf](#)

Declarations of conformity

[DA-DC-00004945.pdf](#)

[DA-DC-00004884.pdf](#)

[DA-DC-00004944.pdf](#)

[DA-DC-00004914.pdf](#)

[DA-DC-00004921.pdf](#)

[DA-DC-00004890.pdf](#)

[DA-DC-00004888.pdf](#)

[DA-DC-00004891.pdf](#)

[DA-DC-00004920.pdf](#)

[DA-DC-00004911.pdf](#)

[DA-DC-00004879.pdf](#)

[DA-DC-00004883.pdf](#)

[DA-DC-00004962.pdf](#)

[DA-DC-00004887.pdf](#)

[DA-DC-00004892.pdf](#)

[DA-DC-00004951.pdf](#)

[DA-DC-00004917.pdf](#)

[DA-DC-00004918.pdf](#)

Drawings

[eaton-manual-motor-starters-busbar-b3-accessory-dimensions-006.eps](#)

[eaton-manual-motor-starters-busbar-b3-accessory-3d-drawing-002.eps](#)

eCAD model

[DA-CE-ETN.B3.0_2-PKZ0](#)

Installation videos

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

WIN-WIN with push-in technology

mCAD model

DA-CD-b3_0_2_pkz0

DA-CS-b3_0_2_pkz0

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia