

Fuse-link, low voltage, 100 A, AC 500 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs



Part no. NH FUSE 100A 500V SIZE 000 GG MGL
100NHG000B
EL Number 1664013
(Norway)

General specifications		
Product name		Eaton Busmann series low voltage NH Fuse
Part no.		NH FUSE 100A 500V SIZE 000 GG MGL
EAN		5027590187268
Product Length/Depth		79 millimetre
Product height		51 millimetre
Product width		21 millimetre
Product weight		119.333 gram
Compliances		CE Marked RoHS Compliant
Certifications		DIN 43620 IEC 60269-2 IEC 60269-1
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Electrical data		
Amperage Rating		100 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gG/gL
Frequency rating - min		45 Hz
Frequency rating - max		62 Hz
Product specifications		
Fuse size		NH000
Insulated metal gripping lugs (IMGL)		No
Accessories		
Suitable for		Microswitch 170H0236 EBF Vertical fuse rail EBV Vertical fuse switch-disconnectors EBH Size 000 Horizontal fuse switch-disconnectors

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss13-27-14-20-05 [AFZ800020])		
Fuse construction type according to IEC 60269		NH000
Voltage type		AC
Rated current	A	100
Rated voltage AC	V	500
Rated switching capacity AC	kA	120
Rated voltage DC	V	
Rated switching capacity DC	kA	
Utilization category		gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	7.4