

Fuse-link, low voltage, 160 A, AC 500 V, NH01, gL/gG, IEC, dual indicator



Part no. NH FUSE 160A 500V GG/GL SIZE 01
160NHG01B
EL Number 1664047
(Norway)

General specifications		
Product name		Eaton Bussmann series low voltage NH Fuse
Part no.		NH FUSE 160A 500V GG/GL SIZE 01
EAN		5027590437257
Product Length/Depth		135 millimetre
Product height		57.8 millimetre
Product width		29.55 millimetre
Product weight		270.667 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC 60269-2 DIN 43620 IEC 60269-1
Product Tradename		None
Product Type		Low voltage NH fuse
Product Sub Type		None
Electrical data		
Amperage Rating		160 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Class		Class gG/gL
Frequency rating - min		45 Hz
Frequency rating - max		62 Hz
Product specifications		
Fuse size		NH01
Insulated metal gripping lugs (IMGL)		No
Accessories		
Suitable for		Microswitch 170H0235

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss13-27-14-20-05 [AFZ800020])		
Fuse construction type according to IEC 60269		NH01
Voltage type		AC
Rated current	A	160
Rated voltage AC	V	500
Rated switching capacity AC	kA	120
Rated voltage DC	V	
Rated switching capacity DC	kA	
Utilization category		gG (cable protection/equipment protection)
Type of fuse status indicator		Combination fuse status indicator
Insulated metal gripping lugs (IMGL)		No
Power loss at rated current	W	12.3