

Fuse-link, LV, 25 A, AC 500 V, 10 x 38 mm, gL/gG, IEC



Powering Business Worldwide™

**Part no.** CYLINDRICAL FUSE 10 x 38 25A GG 500V AC  
**C10G25**  
**EL Number** 1600210  
**(Norway)**

General specifications		
Product name		Eaton Bussmann series low voltage cylindrical fuse
Part no.		CYLINDRICAL FUSE 10 x 38 25A GG 500V AC
EAN		5027590493499
Product Length/Depth		38 millimetre
Product height		10 millimetre
Product width		10 millimetre
Product weight		8.2 gram
Compliances		CE Marked GoST-R RoHS Compliant
Certifications		IEC 60269
Product Tradename		None
Product Type		Low voltage cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		25 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Utilization category		gG (cable protection/equipment protection)
Compatible fuse holder		
Suitable for		CHM Modular fuse holder

### Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		10x38 mm
Voltage type		AC
Rated current	A	25
Rated voltage	V	500
Utilization category		gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	2.6