

Subtile linear luminaire

MODUS SK1500, lenght 580mm, LED 840, white, without switch

Code: SK1500S4ND/B

EAN: 8596099108151



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	1500
Luminaire efficacy (lm/W):	150	Rated lifetime L80/B50 (h):	80000
Degree of protection (IP):	IP40	Color housing:	White
Material housing:	Aluminium	Light source included:	Yes
Suitable for wall mounting:	Yes		
Suitable for surface mounting:	Yes		
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast

Optical system

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal

Dimensions

Length (mm):	590	Width (mm):	35
Height/depth (mm):	58	Size version:	S
Weight (kg):	0,8		

Electrical values

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	No dim function:	Yes