- EV 11 kW adaper
- LCD display
- 5 m cable
- Type 2 connector

Product ID	MEV11DNNNN5T2

TTOGGCTTB	WEVIIDINININISIZ
Charging mode	Level 2
Connector type	Type 2 connector with 5 m cable
Charging control	Plug-and-Charge, Start/stop touch button,
	adjustable between 6 - 16A
IP protection	IP66
Impact strength	IK08
Display	LCD 3.8"
Reports	Energy usage on diplay
Standard and CE certificate	CE certified
Leakage protection	TypeA + DC6mA
Mounting	Wall (optional with bracket)
Efficiency	>99%
Power meter	Integrated
AC power Input rating	3-phase 400V±20% / 1-phase 230V±20%
Rated frequency	50/60 Hz
Input current	32 A / 16 A
Output power	11 kW/ 7.4 kW/ 3.6 kW
Storage temperature	-40 to 75°C ambient
Operating temperature	-30 to 55°C ambient
Operating humidity	Up to 95% non-condensing
Altitude	≤2000m
Electrical protection	Over Load Protection, Short Circuit Protection, Ground Protection, Over-temp Protection
Dimensions mm	455 (h) x260 (w) x150 (d)
Weight kg	4,5
	1,0





## Accessories to mobile adapter

Aluminium wall bracket	MEVA01NWPLATE
Extension 3P16A to 1P Shucko	MEVX01N3PWIRE
Cable holder for wall mount	MEVH01NHANDLE



